

Features

- Wide Single-Supply Voltage Range or Dual Supplies: +2.5 V to +36 V or ± 1.25 V to ± 18 V
- Low Input Bias Current: 1 nA (Max)
- Low Offset Voltage: ± 7.0 mV (Max)
- Input Common-Mode Voltage Range Includes Ground
- Internal Differential Input Voltage Range Equal to the Supply Voltage
- Operating Temperature Range: -40°C to 125°C
- ESD Rating: 3-kV HBM, 1-kV CDM
- Qualified for Automotive Applications with AEC-Q100 Reliability Test

Description

The devices in this series consist of single/dual/quad independent single- or dual-supply voltage comparators on a single monolithic substrate. The common-mode input voltage range includes ground even when operated from a single supply, and the low power supply current drain makes these comparators suitable for battery operation. These types were designed to directly interface with TTL and CMOS. The current drain is independent of the supply voltage. The outputs can be connected to other open-collector outputs to achieve wired-AND relationships.

All devices are specified for the temperature range from -40°C to 125°C .

Applications

- High-Speed Line or Digital Line Receivers
- High-Speed Sampling Circuits
- Peak and Zero-Crossing Detectors
- HEV/EV

Typical Application Circuit




Table of Contents

Features	1
Applications	1
Description	1
Typical Application Circuit	1
Revision History	3
Pin Configuration and Functions	4
Specifications	6
Absolute Maximum Ratings ⁽¹⁾	6
ESD, Electrostatic Discharge Protection.....	6
Thermal Information.....	6
Electrical Characteristics	7
Typical Performance Characteristics.....	8
Application and Implementation	9
Application Information	9
Typical Application.....	9
Tape and Reel Information	11
Package Outline Dimensions	12
SOP8.....	12
TSSOP8.....	13
MSOP8.....	14
SOP14.....	15
TSSOP14.....	16
Order Information	17
IMPORTANT NOTICE AND DISCLAIMER	18

Revision History

Date	Revision	Notes
2023-02-04	Rev.A.0	Initial version.
2023-05-29	Rev.A.1	<p>The following updates are all about the new datasheet formats or typos, and the actual product remains unchanged.</p> <ul style="list-style-type: none">• Updated the symbol of Figure 3 in the Typical Performance Characteristics.• Updated the website address.• Updated the Tape and Reel information.• Updated the status of LM2903A-TS1R-S and LM2903A-VS1R-S.• Finished the Q100 test.
2024-12-18	Rev.A.2	<p>The following updates are all about the new datasheet formats or typos, and the actual product remains unchanged.</p> <ul style="list-style-type: none">• Updated to a new datasheet format.• Updated to a new format of Package Outline Dimensions.• Updated the Tape and Reel Information.
2025-01-23	Rev.A.3	Added pin configuration of TSSOP8.

Pin Configuration and Functions





Table 1. Pin Functions: LM2903A

Pin No.	Name	I/O	Description
1	Out A	O	Output
2	-In A	I	Inverting input
3	+In A	I	Non-inverting input
4	-Vs		Negative power supply
5	+In B	I	Non-inverting input
6	-In B	I	Inverting input
7	Out B	O	Output
8	+Vs		Positive power supply

36-V Low-Power Comparators, Automotive Qualification

Table 2. Pin Functions: LM2901A

Pin No.	Name	I/O	Description
1	Out A	O	Output
2	Out B	O	Output
3	+V _S		Positive power supply
4	-In B	I	Inverting input
5	+In B	I	Non-inverting input
6	-In A	I	Inverting input
7	+In A	I	Non-inverting input
8	-In C	I	Inverting input
9	+In C	I	Non-inverting input
10	-In D	I	Inverting input
11	+In D	I	Non-inverting input
12	-V _S		Negative power supply
13	Out D	O	Output
14	Out C	O	Output

Specifications

Absolute Maximum Ratings ⁽¹⁾

Parameters		Min	Max	Unit
	Supply Voltage: (+V _S) – (–V _S)		40	V
	Voltage on Input and Output Pins	(–V _S) – 0.3	(+V _S) + 0.3	V
	Input Current: +IN, –IN ⁽²⁾	–10	10	mA
	Output Current: OUT	–10	10	mA
	Output Short-Circuit Duration ⁽³⁾		Infinite	
T _J	Maximum Junction Temperature		150	°C
T _A	Operating Temperature Range	–40	125	°C
T _{STG}	Storage Temperature Range	–65	150	°C
T _L	Lead Temperature (Soldering 10 sec)		260	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

(2) The inputs are protected by ESD protection diodes to each power supply. If the input extends more than 500 mV beyond the power supply, the input current should be limited to less than 10 mA.

(3) A heat sink may be required to keep the junction temperature below the absolute maximum. This depends on the power supply voltage and how many amplifiers are shorted. Thermal resistance varies with the amount of PC board metal connected to the package. The specified values are for short traces connected to the leads.

ESD, Electrostatic Discharge Protection

Symbol	Parameter	Condition	Minimum Level	Unit
HBM	Human Body Model ESD	AEC-Q100-002	3	kV
CDM	Charged Device Model ESD	AEC-Q100-011	1	kV

Thermal Information

Package Type	θ _{JA}	θ _{JC}	Unit
SOP8	158	43	°C/W
TSSOP8	191	44	°C/W
MSOP8	210	45	°C/W
SOP14	97	47	°C/W
TSSOP14	108	43	°C/W

36-V Low-Power Comparators, Automotive Qualification
Electrical Characteristics

All test conditions: $V_{CC} = 5\text{ V}$, $R_{PU} = 10\text{ k}\Omega$, $C_L = 15\text{ pF}$, $T_A = 25^\circ\text{C}$, unless otherwise noted.

Parameter		Conditions		Min	Typ	Max	Unit
V_{CC}	Supply Voltage	$T_A = -40^\circ\text{C}$ to 125°C		2.5		36	V
V_{OS}	Input Offset Voltage	$V_{CC} = 5\text{ V}$ to 30 V , $V_{CM} = 0\text{ V}$, $V_O = 1.4\text{ V}$, $T_A = -40^\circ\text{C}$ to 125°C		-7	± 0.6	7	mV
I_B	Input Bias Current ⁽¹⁾	$V_{DM} = 0\text{ V}$, $V_{CM} = 0\text{ V}$			0.1	1	nA
		$V_{DM} = 0\text{ V}$, $V_{CM} = 0\text{ V}$, $T_A = -40^\circ\text{C}$ to 125°C			1	10	nA
I_{OS}	Input Offset Current ⁽¹⁾	$V_{DM} = 0\text{ V}$, $V_{CM} = 0\text{ V}$			0.1	1	nA
		$V_{DM} = 0\text{ V}$, $V_{CM} = 0\text{ V}$, $T_A = -40^\circ\text{C}$ to 125°C			1	10	nA
I_{Diff}	Input Differential Current	$V_{CC} = 36\text{ V}$, $V_{DM} = 36\text{ V}$			50		nA
C_{IN}	Input Capacitance	$T_A = 25^\circ\text{C}$	Differential mode		2.5		pF
			Common mode		5		
V_{CM}	Common-Mode Input Voltage Range			0		$V_{CC} - 1.5$	V
		$T_A = -40^\circ\text{C}$ to 125°C		0		$V_{CC} - 2$	V
A_{VD}	Large-Signal Differential-Voltage Amplification	$V_{CC} = 15\text{ V}$, $V_O = 1.4\text{ V}$ to 11.4 V , $R_L \geq 15\text{ k}\Omega$ to V_{CC}		50	400		V/mV
I_{OH}	High-Level Output Current	$V_{OH} = 5\text{ V}$, $V_{ID} = 1\text{ V}$			25	500	nA
		$V_{CC} = 36\text{ V}$, $V_{OH} = 36\text{ V}$, $V_{ID} = 1\text{ V}$, $T_A = -40^\circ\text{C}$ to 125°C				5	μA
V_{OL}	Low-Level Output Voltage	$I_{OL} = 4\text{ mA}$, $V_{ID} = -1\text{ V}$			250	400	mV
		$I_{OL} = 4\text{ mA}$, $V_{ID} = -1\text{ V}$, $T_A = -40^\circ\text{C}$ to 125°C				600	mV
I_{OL}	Low-Level Output Current	$V_{OL} = 1.5\text{ V}$, $V_{ID} = -1\text{ V}$		10			mA
I_Q	Quiescent Current per Comparator	$V_{CC} = 5\text{ V}$, $T_A = -40^\circ\text{C}$ to 125°C			100	300	μA
		$V_{CC} = 36\text{ V}$, $T_A = -40^\circ\text{C}$ to 125°C			100	300	μA
t_{RT}	Response Time	R_L connected to 5 V through $5.1\text{ k}\Omega$, $C_L = 15\text{ pF}$	100-mV input step with 5-mV overdrive		2		μs
			TTL-level input step		0.5		

(1) Provided by bench tests and design simulation.

Typical Performance Characteristics

All test conditions: $V_S = 5\text{ V}$, $V_{CM} = 0\text{ V}$, $R_L = \text{Open}$, unless otherwise noted.




Figure 1. Supply Current vs. Supply Voltage (Dual Channel)




Figure 2. Response Time for Various Input Overdrives: Positive Transition




Figure 3. Response Time for Various Input Overdrives: Negative Transition




Figure 4. Negative Output Swing vs. Sink Current

Application and Implementation

Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Application Information

Power Supply Layout and Bypass

The power supply pins of the LM2903A/2901A series should have a local bypass capacitor (i.e., 0.01 μF to 0.1 μF) within 2 mm for high-frequency performance. It can also use a bulk capacitor (i.e., 1 μF or larger) within 100 mm to provide large, slow currents. This bulk capacitor can be shared with other analog parts.

A good ground layout improves performance by decreasing the amount of stray capacitance and noise at the inputs and outputs of the comparator. To decrease stray capacitance, minimize PCB lengths and resistor leads, and place external components to the pins of the comparator as close as possible.

Operation Outside of the Common Input Voltage Range

A list of input voltage situation and their outcomes are as follows:

1. When both $-\text{IN}$ and $+\text{IN}$ are both within the common-mode range:
 - a. If $-\text{IN}$ is higher than $+\text{IN}$ and the offset voltage, the output is low, and the output MOSFET is sinking current.
 - b. If $-\text{IN}$ is lower than $+\text{IN}$ and the offset voltage, the output is high impedance.
2. When $-\text{IN}$ is higher than the common mode and $+\text{IN}$ is within the common mode, the output is low, and the output MOSFET is sinking current.
3. When $+\text{IN}$ is higher than the common mode and $-\text{IN}$ is within the common mode, the output is high impedance.
4. When $-\text{IN}$ and $+\text{IN}$ are both higher than the common mode, the output is in an uncertain state.

Typical Application

IR Receiver

The device is an ideal candidate to be used as an infrared receiver shown in [Figure 5](#). The infrared photo diode creates a current relative to the amount of infrared light present. The current creates a voltage across R_D . When this voltage level crosses the voltage applied by the voltage divider to the inverting input, the output transitions. Optional R_O provides additional hysteresis for noise immunity.





Figure 5. IR Receiver

Tape and Reel Information





Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm) ⁽¹⁾	B0 (mm) ⁽¹⁾	K0 (mm) ⁽¹⁾	P0 (mm)	W0 (mm)	Pin1 Quadrant
LM2903A-SO1R-S	SOP8	330.0	17.6	6.5	5.4	2.0	8.0	12.0	Q1
LM2903A-TS1R-S	TSSOP8	330.0	17.6	6.8	3.3	1.7	8.0	12.0	Q1
LM2903A-VS1R-S	MSOP8	330.0	17.6	5.2	3.3	1.5	8.0	12.0	Q1
LM2901A-SO2R-S	SOP14	330.0	21.6	6.5	9.1	1.8	8.0	16.0	Q1
LM2901A-TS2R-S	TSSOP14	330.0	17.6	6.8	5.5	1.7	8.0	12.0	Q1

(1) The value is for reference only. Contact the 3PEAK factory for more information.

Package Outline Dimensions

SOP8







TSSOP8
Package Outline Dimensions
TS1(TSSOP-8-A)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.900	1.200	0.035	0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D	2.900	3.100	0.114	0.122
E	6.200	6.600	0.244	0.260
E1	4.300	4.500	0.169	0.177
e	0.650 BSC		0.026 BSC	
L	0.450	0.750	0.018	0.030
θ	0	8°	0	8°

NOTES




1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

MSOP8
Package Outline Dimensions
VS1(MSOP-8-A)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.800	1.100	0.031	0.043
A1	0.020	0.150	0.001	0.006
A2	0.750	0.950	0.030	0.037
b	0.250	0.380	0.010	0.015
c	0.090	0.230	0.004	0.009
D	2.900	3.100	0.114	0.122
E	4.700	5.100	0.185	0.201
E1	2.900	3.100	0.114	0.122
e	0.650 BSC		0.026 BSC	
L	0.400	0.800	0.016	0.031
θ	0	8°	0	8°

NOTES




1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

SOP14
Package Outline Dimensions
SO2(SOP-14-A)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.350	1.750	0.053	0.069
A1	0.050	0.250	0.002	0.010
A2	1.250	1.650	0.049	0.065
b	0.310	0.510	0.012	0.020
c	0.100	0.250	0.004	0.010
D	8.450	8.850	0.333	0.348
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
e	1.270 BSC		0.050 BSC	
L	0.400	1.270	0.016	0.050
θ	0	8°	0	8°

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

TSSOP14
Package Outline Dimensions
TS2(TSSOP-14-A)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.900	1.200	0.035	0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D	4.900	5.100	0.193	0.201
E	6.200	6.600	0.244	0.260
E1	4.300	4.500	0.169	0.177
e	0.650 BSC		0.026 BSC	
L	0.450	0.750	0.018	0.030
θ	0	8°	0	8°

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

Order Information

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
LM2903A-SO1R-S	-40 to 125°C	SOP8	2903S	3	Tape and Reel, 4000	Green
LM2903A-TS1R-S	-40 to 125°C	TSSOP8	2903S	3	Tape and Reel, 3000	Green
LM2903A-VS1R-S	-40 to 125°C	MSOP8	2903S	3	Tape and Reel, 3000	Green
LM2901A-SO2R-S	-40 to 125°C	SOP14	2901S	3	Tape and Reel, 2500	Green
LM2901A-TS2R-S	-40 to 125°C	TSSOP14	2901S	3	Tape and Reel, 3000	Green

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2025. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.