

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Features

- Wide Input Voltage Range: 2.5 V to 5.5 V
- Output Adjustable from 0.6 V to the Input Voltage
- Low 100-nA (Typical) Shutdown Current and 25- μ A (Typical) Quiescent Current
- 0.6 V $\pm$ 1% Reference Voltage Accuracy
- Power-Save Mode or Forced-PWM Mode Version Available
- 1.1 MHz Switching Frequency
- Integrated 65-m Ω High-Side and 30-m Ω Low-Side Power MOSFETs
- Internal Soft Start-up with Pre-bias Output
- Enable Compatible with 1.2-V I/O Input
- 100% Duty Cycle Mode Operation
- Cycle-by-Cycle Current Limit and Hiccup When Overload or Short Circuit
- Available in the SOT563 (1.6 mm*1.6 mm) Package

Applications

- Router, Switch, and Access Point
- IP Camera, Drone
- TV, DVR, STB
- General Purpose Power Supply

Description


The TPP05302 is an easy-to-use, high-efficiency, synchronous, step-down regulator with integrated high-side and low-side MOSFETs. It provides up to 3-A output current and operates over a wide input voltage range.

The TPP05302 operates over a wide input voltage range from 2.5 V to 5.5 V with 25- μ A ultra-low quiescent current. It is ideal for battery-powered systems due to its low quiescent current. The TPP05302 employs an adaptive- off time with peak current control for fast loop response, simple loop design, and external components. The TPP05302 series supports power-saving mode to improve efficiency in light-load operation and forced-PWM mode to maintain a fixed switching frequency and reduce output ripple during all load conditions.

The TPP05302 has built-in robust protections such as thermal shutdown, UVLO, and enable (EN) control. Additionally, during overload or short-circuit conditions, the cycle-by-cycle current limit and hiccup protection are provided. Thermal shutdown provides reliable and fault-tolerant operation.

The TPP05302 is available in the SOT563 (1.6 mm*1.6 mm) package.

Typical Application Circuit



**2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the
SOT563 Package**

Table of Contents

Features	1
Applications	1
Description	1
Typical Application Circuit	1
Product Family Table	3
Revision History	3
Pin Configuration and Functions	4
Specifications	5
Absolute Maximum Ratings ⁽¹⁾	5
ESD, Electrostatic Discharge Protection.....	5
Recommended Operating Conditions.....	5
Thermal Information.....	5
Electrical Characteristics.....	6
Typical Performance Characteristics.....	7
Detailed Description	8
Overview.....	8
Functional Block Diagram.....	8
Feature Description.....	9
Application and Implementation	10
Application Information.....	10
Application Waveforms.....	13
Layout	17
Layout Guideline.....	17
Layout Recommendations.....	17
Tape and Reel Information	18
Package Outline Dimensions	19
SOT563-6.....	19
Order Information	20
IMPORTANT NOTICE AND DISCLAIMER	21

**2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the
SOT563 Package****Product Family Table**

Order Number	Light Load Mode
TPP053022-S56R	Power-Save Mode
TPP053023-S56R	Forced-PWM Mode

Revision History

Date	Revision	Notes
2025-08-15	Rev A.0	Initial released.

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Pin Configuration and Functions




Table 1. Pin Functions: TPP05302

Pin	Name	I/O	Description
1	GND	G	Ground pin. Power and controller circuit ground. Use a star connection to the GND pin with good contact.
2	SW	O	Switching output pin. Connect this pin to the external inductor.
3	VIN	I	Input voltage supply pin. Input capacitors should be placed as close to this pin and the PGND pin as possible.
4	EN	I	Enable input pin. The input signal to turn the regulator on or off, High = on, Low = off.
5	FB	I	Voltage feedback pin. Connect to the middle point of a feedback resistor divider to set the output value.
6	OUT	O	Output sense pin. This pin is the voltage power rail and input sense for the output voltage. An output capacitor is needed to decrease the output voltage ripple.

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Specifications

Absolute Maximum Ratings ⁽¹⁾

Parameter		Min	Max	Unit
V _{IN}	Supply Voltage	-0.3	6	V
SW	Switching Node Voltage	-0.3	V _{IN} + 0.3	V
SW	Switching Node Voltage (10 ns Transient)	-3	10	V
OUT	Output Sense Voltage	-0.3	6	V
FB	Feedback Voltage	-0.3	6	V
EN	Enable Input	-0.3	6	V
T _A	Operating Temperature Range	-40	150	°C
T _{STG}	Storage Temperature Range	-55	150	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

ESD, Electrostatic Discharge Protection

Symbol	Parameter	Condition	Minimum Level	Unit
HBM	Human Body Model ESD	ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	±2000	V
CDM	Charged Device Model ESD	ANSI/ESDA/JEDEC JS-002 ⁽²⁾	±500	V

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

Recommended Operating Conditions

Parameter		Min	Max	Unit
V _{IN}	Supply Voltage	2.5	5.5	V
V _{EN}	Enable Input Voltage	0	V _{IN}	V
V _{OUT}	Output Voltage	0.6	V _{IN}	V
T _A	Ambient Temperature	-40	125	°C

Thermal Information

Package Type	θ _{JA}	θ _{JB}	θ _{Jc}	Unit
SOT563	143.8	16.7	88.2	°C/W

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Electrical Characteristics

Unless otherwise noted, the min and max limits apply over the recommended operating ambient temperature range (T_A) of -40°C to 125°C . Typical values are measured under $V_{\text{IN}} = 5\text{ V}$ and $T_A = 25^{\circ}\text{C}$ and represent the most likely parameters normally for reference.

Parameter		Condition	Min	Typ	Max	Unit
Power Supply						
V_{IN}	Supply Voltage Range		2.5		5.5	V
$V_{\text{IN_UV}}$	Under Voltage Lockout Thresholds	Rising Threshold	2.3	2.4	2.5	V
		Falling Threshold		2.3		V
I_{SD}	Shutdown Supply Current	$V_{\text{EN}} = 0\text{ V}$		0.1		μA
I_{Q}	Non-Switching Quiescent Current	$V_{\text{EN}} = \text{High}$, Non-Switching		25		μA
Enable						
$V_{\text{EN_H}}$	Enable High Threshold	Rising Threshold			0.88	V
$V_{\text{EN_L}}$	Enable Low Threshold	Hysteresis	0.33			V
$I_{\text{EN_LKG}}$	Enable Input Leakage Current	$V_{\text{EN}} = \text{High}$		10		nA
Soft Start						
T_{SS}	Internal Soft-Start Time			800		μs
Voltage Reference						
V_{FB}	Feedback Voltage	$2.5\text{ V} \leq V_{\text{IN}} \leq 5.5\text{ V}$	594	600	606	mV
V_{FB}	Feedback Voltage	$T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$	588	600	612	mV
$I_{\text{FB_LKG}}$	Feedback Input Leakage Current	$V_{\text{FB}} = 0.6\text{ V}$		10		nA
MOSFETs						
$R_{\text{DS(on)_H}}$	High Side MOSFET ON Resistance	$V_{\text{IN}} = 5\text{ V}$		65		m Ω
$R_{\text{DS(on)_L}}$	Low Side MOSFET ON Resistance	$V_{\text{IN}} = 5\text{ V}$		30		m Ω
Current Limits						
$I_{\text{LIMIT_H}}$	High Side Current Limit	Inductor Peak Current, $V_{\text{IN}} = 3.3\text{ V}$	3.8	4.6	5.6	A
$I_{\text{LIMIT_L}}$	Low Side Current Limit	Inductor Valley Current, $V_{\text{IN}} = 3.3\text{ V}$		4.3		A
$I_{\text{LIMIT_N}}$	Negative Current Limit			-2		A
Output Discharge						
I_{DISCHG}	Output Discharge Current on SW	$V_{\text{IN}} = 3\text{ V}$, $V_{\text{OUT}} = 2\text{ V}$		90		mA
Switching Frequency Timing						
f_{SW}	Switching Frequency, FPWM Mode	$V_{\text{IN}} = 5\text{ V}$, $V_{\text{OUT}} = 1.8\text{ V}$		1100		kHz
Thermal Shutdown						
T_{SD}	Thermal Shutdown			160		$^{\circ}\text{C}$
$T_{\text{SD_HYS}}$	Thermal Shutdown Hysteresis			20		$^{\circ}\text{C}$

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Typical Performance Characteristics

All test conditions: $V_{IN} = 5\text{ V}$, $V_{OUT} = 1.8\text{ V}$, PFM mode, $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted.




Figure 1. Non-Switching Quiescent Current




Figure 2. Feedback Voltage




Figure 3. High-Side and Low-Side MOSFET




Figure 4. Switching Frequency

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Detailed Description

Overview

The TPP05302 is an easy-to-use, high-efficiency, synchronous, step-down regulator with integrated high-side and low-side MOSFETs. It provides up to 3 A of output current and operates over a wide input voltage range.

The TPP05302 operates over a wide input voltage range from 2.5 V to 5.5 V with 25- μ A ultra-low quiescent current. It is ideal for battery-powered systems due to its low quiescent current. The TPP05302 employs an adaptive off-time with a peak current control for fast loop response, simple loop design, and external components. The TPP05302 series supports power-saving mode to improve efficiency in light-load operation and forced-PWM mode to maintain a fixed switching frequency and reduce output ripple during all load conditions.

The TPP05302 has built-in robust protections such as thermal shutdown, UVLO, and enable (EN) control. Additionally, during overload or short-circuit conditions, the cycle-by-cycle current limit and hiccup protection are provided. Thermal shutdown provides reliable and fault-tolerant operation.

Functional Block Diagram




Figure 5. Functional Block Diagram

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Feature Description

Adaptive-off Time with Peak Current Control

The TPP05302 adopts adaptive-off time with peak current control. The feedback voltage is sensed from the resistor divider through the FB pin to compare with the internal voltage reference. The required off time for the low-side MOSFET is calculated based on the input and output voltage, making the switching frequency relatively constant regardless of different duty cycles and load current.

Light Load Operation

The TPP05302 integrates two behaviors in light-load operation. One behavior is power-saving mode (PSM) control to improve efficiency in light-load working conditions. When the load current decreases, the device approaches discontinuous conduction mode and the low-side MOSFET is turned off when the zero-current detection is triggered to improve system efficiency. In this operation, the device reduces the switching frequency and minimizes the current consumption. In power-saving mode, the output voltage rises slightly above the nominal output voltage. This effect is minimized by increasing the output capacitor or adding a feedforward capacitor.

The other behavior is forced-PWM mode (FPWM) to optimize the output ripple. In FPWM mode, the device operates in continuous conduction mode during light load operation, and the switching frequency is almost constant over the entire load range. To maintain the switching frequency, a limited negative current is allowed to flow through the inductor and low-side power switch.

100% Duty Cycle Operation

The TPP05302 offers a low input-to-output voltage difference by entering 100% duty cycle operation. In this operation, the high-side MOSFET is constantly turned on, and the low-side MOSFET is switched off.

Soft-Start with Pre-Biased Capability

The TPP05302 implements a soft-start circuit to prevent the inrush current during start-up. The soft-start time is fixed internally. When the start-up period begins, the internal reference voltage slowly ramps up.

The TPP05302 also supports a monotonic start-up with pre-biased loads. If the output voltage is pre-biased to a certain value during start-up, the device disables switching for both high-side and low-side power switches until the soft-start reference voltage exceeds the feedback voltage.

Undervoltage Lockout (UVLO) Protection

Once the input voltage falls below the UVLO threshold, the device is shut off. Once the device recovers above the UVLO threshold, the device returns to normal operation.

Current Limits

The TPP05302 employs both cycle-by-cycle peak and valley current limits to protect the high-side and low-side MOSFET overloaded. Once the inductor current reaches the high-side peak current limit, the high-side switch is turned off immediately to avoid the inductor current from further increasing. When the low-side valley current limit is triggered, the next duty cycle is held until the inductor current recovers within the valley current limit. Both peak and valley current limits determine the device's maximum output current, and the valley current limit can prevent inductor current from running away during unexpected overload or short-circuit conditions. Also, the device integrates one zero-current detector to turn off the low-side MOSFET at light loads in the PFM version.

Thermal Shutdown

Once the junction temperature rises above the internal over-temperature shutdown threshold, the device shuts off and recovers when the temperature falls below the threshold with hysteresis.

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Application and Implementation

Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Application Information

The TPP05302 is typically used to convert a wide range of input voltages to the desired output voltage, which can be set by the feedback resistor dividers. Some typical parameters and external component values are recommended to help speed up the development process. In most power systems, a lower voltage rail, such as 1.2 V/1.8 V, is typically used for microcontrollers, I/Os, and other low-voltage components.




Figure 6. Typical Application Circuit

Setting Output Voltage

The external resistor divider network connected to the FB pin sets the output voltage. The resistance of the divider is a compromise between noise suppression and output current consumption. The smaller-value resistor will reduce noise sensitivity but will also increase the system's quiescent current and reduce light load efficiency. Once the top feedback resistor is selected, the feedback resistors value can be calculated with the following equation.

$$R_{FBB} = \frac{V_{FB} * R_{FBT}}{V_{OUT} - V_{FB}} \quad (1)$$

where V_{FB} is the internal reference voltage which is typically 0.6 V for TPP05302.

Inductor Selection

The selection of the inductor affects steady-state operation as well as transient behavior and loop stability. These factors make it the most important component in power regulator design. There are three important inductor specifications: inductance value, DC resistance, and saturation current. The inductance value is designed based on the desired peak-to-peak ripple current and is typically chosen to be in the range of 20% to 40% of the maximum output current. Once the desired inductor ripple current is selected, the inductor value can be calculated with the following equation.

$$L = \frac{V_{OUT}}{f_{SW} * \Delta I_L} * \left(1 - \frac{V_{OUT}}{V_{IN}}\right) \quad (2)$$

where f_{SW} is the switching frequency and ΔI_L is the inductor ripple current.

When the inductor current approaches its saturation level, the effective inductance can fall to a fraction of the zero current value. Although one high-side valley current limit is integrated to avoid the current run-away, the inductor current can rise

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

to a high value very rapidly if the inductor is saturated. The inductor saturation current must leave a safe margin from the high-side peak current limit in the worst-case conditions. The inductor's RMS current and peak current can be calculated with the equation below.

$$I_{L_PEAK} = I_{OUT} + \frac{\Delta I_L}{2} \quad (3)$$

$$I_{L_RMS} = \sqrt{I_{OUT}^2 + \frac{\Delta I_L^2}{12}} \quad (4)$$

Input Capacitor Selection

The input capacitor of the step-down converter is used to supply the AC input current and maintain a stable DC input voltage. At least a 10-μF capacitance of ceramic input capacitor is recommended. Additional input capacitance may be required to meet ripple and/or transient requirements. High-quality ceramic, X5R or X7R, is recommended because of its low ESR characteristic and small capacitance variations over the temperature range. In addition, one small value and small case size, ceramic capacitor (such as 100nF, 0603 package) is recommended to be used at the input and be placed as close as possible to the VIN and GND pins. This can provide a high -frequency bypass for the internal control circuits. The input capacitor can be calculated with the equation below when the input voltage ripple is determined.

$$\Delta V_{IN} = \frac{I_{OUT}}{f_{SW} * C_{IN}} * \frac{V_{OUT}}{V_{IN}} * \left(1 - \frac{V_{OUT}}{V_{IN}}\right) \quad (5)$$

where C_{IN} is the input capacitance value.

The input capacitor ripple current rating should be greater than the maximum input current ripple. The RMS current of the input capacitor can be calculated with the following equation.

$$I_{CIN_RMS} = I_{OUT} * \sqrt{\frac{V_{OUT}}{V_{IN}} * \left(1 - \frac{V_{OUT}}{V_{IN}}\right)} \quad (6)$$

The worst case for the input voltage ripple and RMS current occurs when the duty cycle is 50%.

Output Capacitor Selection

The output capacitance is mainly selected to meet the requirement of the output ripple and voltage change during a load transient. Then the control loop is compensated for the selected output capacitor. The output voltage ripple is related to the capacitance and equivalent series resistance (ESR) of the output capacitor. Assuming the capacitor has a small ESR, the minimum output capacitance needed for a given output ripple voltage can be calculated with the equation below.

$$C_{OUT} > \frac{\Delta I_L}{8 * f_{SW} * \Delta V_{OUT}} \quad (7)$$

where ΔI_L is the inductor ripple current, and ΔV_{OUT} is the output voltage ripple.

If high ESR capacitors are used, they will contribute additional output ripple. ESR ripple can be neglected for ceramic capacitors but must be considered if electrolytic capacitors are used. The maximum ESR for a given ripple can be calculated with the equation below.

$$R_{ESR} < \frac{\Delta V_{OUT}}{\Delta I_L} - \frac{1}{8 * f_{SW} * C_{OUT}} \quad (8)$$

The effective value of the ceramic capacitor decrease should be considered when the output DC bias voltage is added across the capacitors. The RMS current of the output capacitor can be calculated with the following equation.

$$I_{COUT_RMS} = \frac{V_{OUT} * (V_{IN_MAX} - V_{OUT})}{\sqrt{12} * V_{IN_MAX} * L * f_{SW}} \quad (9)$$

where V_{IN_MAX} is the maximum input voltage, and L is the selected inductor value.


**2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the
SOT563 Package****Feed Forward Capacitor Selection**

A feed-forward capacitor reduces the output ripple in PFM mode and improves the load transient response. A 120-pF feed-forward capacitor is recommended for the 1.8-V output in the typical application.


2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Application Waveforms


All test conditions: $V_{IN} = 5\text{ V}$, $V_{OUT} = 1.8\text{ V}$, PFM mode, $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted.




FPWM Mode
Figure 7. Efficiency




PFM Mode
Figure 8. Efficiency




$V_{IN} = 3.6\text{ V}$, FPWM Mode
Figure 9. Efficiency



$V_{IN} = 3.6\text{ V}$, PFM Mode
Figure 10. Efficiency




FPWM Mode
Figure 11. Load Regulation




PFM Mode
Figure 12. Load Regulation

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package




FPWM Mode

Figure 13. Line Regulation




PFM Mode

Figure 14. Line Regulation




$I_{OUT} = 0.1\text{ A}$, FPWM Mode

Figure 15. Switching Waveform and Output Ripple




$I_{OUT} = 0.1\text{ A}$, PFM Mode

Figure 16. Switching Waveform and Output Ripple





$I_{OUT} = 1.5\text{ A}$

Figure 17. Switching Waveform and Output Ripple











$I_{OUT} = 3\text{ A}$

Figure 18. Switching Waveform and Output Ripple



2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

 $I_{OUT} = 0.1\text{ A to }3\text{ A to }0.1\text{ A, FPWM Mode}$
Figure 19. Load Transient

 $I_{OUT} = 0\text{ A, FPWM Mode, Entry}$
Figure 21. Short Circuit Protection

 $I_{OUT} = 0\text{ A, PFM Mode, Entry}$
Figure 23. Short Circuit Protection

 $I_{OUT} = 3\text{ A, Entry}$
Figure 25. Short Circuit Protection

 $I_{OUT} = 0.1\text{ A to }1.5\text{ A to }0.1\text{ A, FPWM Mode}$
Figure 20. Load Transient

 $I_{OUT} = 0\text{ A, FPWM Mode, Recovery}$
Figure 22. Short Circuit Protection

 $I_{OUT} = 0\text{ A, PFM Mode, Recovery}$
Figure 24. Short Circuit Protection

 $I_{OUT} = 3\text{ A, Recovery}$
Figure 26. Short Circuit Protection


2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

 $I_{OUT} = 0\text{ A}$, FPWM Mode

Figure 27. Power up by Enable



 $I_{OUT} = 0\text{ A}$, PFM Mode

Figure 29. Power up by Enable



 $I_{OUT} = 3\text{ A}$, FPWM Mode

Figure 31. Power up by Enable


 $I_{OUT} = 0\text{ A}$, FPWM Mode

Figure 28. Power down by Enable



 $I_{OUT} = 0\text{ A}$, PFM Mode

Figure 30. Power down by Enable



 $I_{OUT} = 3\text{ A}$, FPWM Mode

Figure 32. Power down by Enable



2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Layout

Layout Guideline

The performance of switching converters heavily depends on the quality of the PCB layout. especially for thermal design and EMI design. Even if the schematic design is good, a bad PCB layout can disrupt the converter's operation.

1. Place a low ESR ceramic capacitor as close to the VIN pin and the ground as possible.
2. Make sure the top switching loop with power has the lowest impedance to ground.
3. The output inductor should be placed close to the SW pin to minimize the SW area.
4. The FB terminal is sensitive to noise so the feedback resistor should be located as close as possible to the IC.
5. Keep the connection of the input capacitor and VIN as short and wide as possible.

Layout Recommendations






Figure 33. Layout Example

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Tape and Reel Information




Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	W0 (mm)	Pin1 Quadrant
TPP053022-S56R	SOT563	180	13.1	1.78	1.78	0.69	4.0	8.0	Q3
TPP053023-S56R	SOT563	180	13.1	1.78	1.78	0.69	4.0	8.0	Q3

2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Package Outline Dimensions

SOT563-6



2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the SOT563 Package

Order Information

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPP053022-S56R	-40 to 125°C	SOT563	536	MSL3	Tape and Reel, 5000	Green
TPP053023-S56R	-40 to 125°C	SOT563	537	MSL3	Tape and Reel, 5000	Green

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

**2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the
SOT563 Package****IMPORTANT NOTICE AND DISCLAIMER**

Copyright© 3PEAK 2012-2026. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.

**2.5-V to 5.5-V Input, 3-A Synchronous Step-Down Regulator in the
SOT563 Package**

This page intentionally left blank