

Features

- 16-V to 170-V Input Voltage Range
- Selectable 12-V, 15-V, and 18-V Output Voltages
- Programmable Output Voltage from 3.3 V to 26 V
- 0.5-A Output Current Capability
- High-Voltage Startup
- High Efficiency with PFM Mode at Light Loads
- 12-ms Soft Startup Time
- 100-kHz Switching Frequency
- VDD Under-voltage Protection
- Over Load Protection
- Output Short-circuit Protection
- Cycle-by-cycle Current Limit
- Operating Temperature Range from -40°C to $+150^{\circ}\text{C}$
- Available in the SOP8 Package

Applications

- PoE
- E-Bike
- E-Tools
- Scooter
- Solar Energy

Description

The TPP15052 is a wide input range, non-synchronous DC-DC buck converter that uses peak current mode control. The TPP15052 integrates a 170-V, 1.3- Ω power MOSFET with 1.5-A peak current limit having up to 0.5-A output current capability.

The TPP15052 has a high-voltage startup circuitry to enable the device from high input voltage directly. The TPP15052 has a built-in 12-ms soft-start time to minimize the inrush current during startup. In the moderate to heavy load condition, the TPP15052 works in PWM mode at 100-kHz switching frequency. In the light load condition, the TPP15052 enters PFM mode to reduce the switching loss and improve the efficiency. The TPP15052 also has spread spectrum switching frequency dithering to reduce the EMI.

The TPP15052 features a cycle-by-cycle current limit in over-load conditions. Furthermore, when the output voltage is 10% below the regulation target and the current limit is touched for 128 switching cycles, or the output is short to ground, the TPP15052 enters hiccup mode and stops PWM switching for 65 ms. After hiccup times out, the TPP15052 restarts the soft startup.

The TPP15052 is available in the SOP8 package.

Typical Application Circuit




Table of Contents

Features	1
Applications	1
Description	1
Typical Application Circuit	1
Product Family Table	3
Revision History	3
Pin Configuration and Functions	4
Specifications	5
Absolute Maximum Ratings ⁽¹⁾	5
ESD, Electrostatic Discharge Protection.....	5
Recommended Operating Conditions.....	5
Thermal Information.....	5
Electrical Characteristics.....	6
Typical Performance Characteristics.....	8
Detailed Description	11
Overview.....	11
Functional Block Diagram.....	11
Feature Description.....	11
Application and Implementation	14
Application Information	14
Typical Application.....	14
Application Examples.....	15
Layout	16
Layout Guideline.....	16
Layout Example.....	16
Tape and Reel Information	18
Package Outline Dimensions	19
SOP8.....	19
Order Information	20
IMPORTANT NOTICE AND DISCLAIMER	21

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode**Product Family Table**

Order Number	Feature	Package
TPP15052	Buck Converter	SOP8

Revision History

Date	Revision	Notes
2026-05-12	Rev.A.0	Initial release

Pin Configuration and Functions




Table 1. Pin Functions: TPP15052

Pin		I/O/P	Description
No.	Name		
1	GND	GND	Ground of the output voltage
2,6	NC	-	No connection
3	FB	I	The feedback input of the output voltage when using an external feedback resistor divider. When using internal fixed output setting, leave the FB pin floating or connect it to the ICGND pin.
4	VDD	P	Power supply for the internal control circuitry
5	VIN	I	Drain of the switch MOSFET
7	VSET	P	Output voltage setting pin. Leave the VSET pin floating to select the fixed 12-V output voltage. Connect the VSET pin to the ICGND pin to select the fixed 15-V output voltage. Connect a 51-k Ω resistor between the VSET pin and the ICGND pin to select the fixed 18-V output voltage. Connect a 150-k Ω between the VSET pin and the ICGND pin to set the output voltage by an external resistor divider.
8	ICGND	O	Source of the switch MOSFET. It is also the ground of the internal control circuitry.

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode**Specifications****Absolute Maximum Ratings ⁽¹⁾**

Parameter		Min	Max	Unit
Voltage Range at Terminals (refer to the ICGND pin)	V _{IN}	-0.3	180	V
	V _{DD}	-0.3	26	V
	V _{SET} , FB	-0.3	6	V
	GND	-200	1.5	V
T _J	Maximum Junction Temperature	-40	150	°C
T _A	Operating Temperature Range	-40	125	°C
T _{STG}	Storage Temperature Range	-65	150	°C
T _L	Lead Temperature (Soldering 10 sec)		260	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

ESD, Electrostatic Discharge Protection

Parameter		Condition	Minimum Level	Unit
V _{HBM}	Human Body Model ESD	ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	2000	V
V _{CDM}	Charged Device Model ESD	ANSI/ESDA/JEDEC JS-002 ⁽²⁾	500	V

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

Recommended Operating Conditions

Parameter		Min	Typ	Max	Unit
V _{IN}	Power Supply	16		170	V
V _{OUT}	Output Voltage	3.3		26	V
C _{OUT}	Effective Capacitance for Output	220	470	1000	μF
L	Inductor	47	220	470	μH
T _J	Junction Temperature Range	-40		125	°C

Thermal Information

Package Type	θ _{JA}	θ _{JB}	θ _{JC(TOP)}	Unit
SOP8	109.0	80.3	54.1	°C/W

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode

Electrical Characteristics

All test conditions: $V_{IN} = 48\text{ V}$, $V_{DD} = 12\text{ V}$, $T_J = -40^\circ\text{C}$ to 125°C , unless otherwise noted. Typical values are at $T_J = 25^\circ\text{C}$.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
VIN Supply Voltage and Current						
V_{IN}	IC Supply Voltage Range		16		170	V
I_{HVC}	High Voltage Operating Quiescent Current	$V_{DD} = 0\text{ V}$, $V_{IN} = 150\text{ V}$		4		mA
I_{HVS}	High Voltage Shutdown Current	$V_{DD} = 18\text{ V}$, $V_{IN} = 150\text{ V}$		6		μA
VDD Regulator						
V_{DD}	VDD Voltage Range	After startup	6.5		21	V
I_{DD}	Quiescent Current	Switching mode		0.9		mA
V_{DD_C}	VDD Internal Charging Termination Voltage			9.5		V
V_{DD_UVLO}	VDD UVLO Rising Threshold		7.5	8	8.5	V
$V_{DD_UVLO_HYS}$	VDD UVLO Hysteresis			2		V
V_{DD_CLMP}	VDD Clamp Voltage	$I_{DD_CLMP} = 10\text{ mA}$	21	22.5	24	V
I_{DD_CLMP}	VDD Sinking Current at Clamp Voltage		8	10		mA
Reference Voltage						
V_{REF}	Reference Voltage at the REF Pin	$T_J = -40^\circ\text{C} - 125^\circ\text{C}$	0.965	1.01	1.045	V
Power MOSFET Switch						
$R_{DS(on)}$	N-channel 180-V MOSFET on-Resistance			1.3		Ω
I_{LIM}	Peak Current Limit	$T_A = 25^\circ\text{C}$	1	1.5	2.0	A
I_{SW_LKG}	N-channel MOSFET Leakage Current	$V_{DD} = 5\text{ V}$, $V_{IN} = 150\text{ V}$		6		μA
Rectifier Diode						
V_{BR}	Breakdown Voltage	$I_R = 5\text{ }\mu\text{A}$	200			V
V_F	Forward Voltage	$I_F = 500\text{ mA}$		1	1.5	V
I_F	Maximum Average Forward Rectified Current		0.5			A
Soft Start						
t_{SS}	Soft Startup Time			12		ms
Hiccup Time						
t_{HICCUP}	Hiccup Delay Time			65		ms
Switching Frequency						

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
f_{SW}	Switching Frequency		75	100	125	kHz
Δf_{DITHER}	Switching Frequency Dithering Range			$\pm 6\%$		
t_{MIN_OFF}	Minimum OFF Time			500		ns
t_{MIN_ON}	Minimum ON Time			500		ns
Thermal Protection						
T_{SD}	Thermal Shutdown Protection Threshold	T_J rising		175		$^{\circ}\text{C}$
T_{SD_HYS}	Thermal Shutdown Hysteresis	T_J falling below T_{SD}		25		$^{\circ}\text{C}$

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode

Typical Performance Characteristics

All test conditions: $V_{IN} = 48\text{ V}$, $V_{DD} = 12\text{ V}$, $T_A = +25^\circ\text{C}$, unless otherwise noted.




Figure 1. Efficiency vs. Load Current




Figure 2. Efficiency vs. Load Current




Figure 3. Output Voltage vs. Load Current




Figure 4. Output Voltage vs. Temperature




Figure 5. FB Reference Voltage vs. Temperature




Figure 6. $R_{DS(on)}$ vs. Temperature

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode




Figure 7. VDD UVLO vs. Temperature




Figure 8. Minimum OFF Time vs. Temperature




Figure 9. Current Limit vs. Temperature





Figure 10. Quiescent Current vs. Temperature




Figure 11. Startup Waveform



$V_{IN} = 48\text{ V}$, $V_{OUT} = 15\text{ V}$, $I_{OUT} = 0.7\text{ mA}$

Figure 12. Switching Waveform in Hiccup Mode

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode



$V_{IN} = 48\text{ V}$, $V_{OUT} = 15\text{ V}$, $I_{OUT} = 100\text{ mA}$

Figure 13. Switching Waveform in DCM Mode



$V_{IN} = 48\text{ V}$, $V_{OUT} = 15\text{ V}$, $I_{OUT} = 500\text{ mA}$

Figure 14. Switching Waveform in CCM Mode

Detailed Description

Overview

The TPP15052 is a wide input range, asynchronous DC-DC buck converter that uses peak current mode control. The TPP15052 integrates a 170-V, 1.3- Ω power MOSFET with 1.5-A peak current limit having up to 0.5-A output current capability.

The TPP15052 has a high-voltage startup circuitry to enable the device from high input voltage directly. The TPP15052 has a built-in 12-ms soft-start time to minimize the inrush current during startup. In the moderate to heavy load condition, the TPP15052 works in PWM mode at 100-kHz switching frequency. In the light load condition, the TPP15052 enters PFM mode to reduce the switching loss and improve efficiency. The TPP15052 also has spread spectrum switching frequency dithering to reduce the EMI.

Functional Block Diagram




Figure 15. Functional Block Diagram

Feature Description

High Voltage Startup and VDD UVLO

The TPP15052 integrates a high-voltage startup circuitry. When the VIN pin is applied with a voltage above 16 V, an internal current source starts charging the capacitor at the VDD pin to 9.5 V. When the VDD voltage is above the UVLO threshold of

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode

the 8 V, the device starts switching. The power switch between the VIN pin and the ICGND pin is turned on and the current goes from the VIN pin to the ICGND pin.

When the VDD voltage is below 6 V, the TPP15052 is disabled.

Soft Startup

The TPP15052 has a built-in 12-ms soft start time. When the PWM switching starts, the output of the internal error amplifier increases slowly. The current of the power switch is limited to eliminate the inrush current during startup. During the soft startup, the hiccup mode is disabled. Once the output voltage is above 95% of the regulation voltage or a 32-ms timer for soft startup times out, the hiccup mode is enabled.

PWM mode and PFM Mode

In heavy load, the TPP15052 works in PWM mode. The switching frequency is fixed at 100 kHz. As the load decreases, the PWM switching operation goes from CCM mode to DCM mode.

At the light load, the PWM duty cycle goes to a minimum on-time limit as the load current decreases. The TPP15052 enters PFM mode. The switching frequency gradually changes from 100 kHz to 35 kHz to regulate the output voltage. When the switching frequency reaches 35 kHz but the load current continues decreasing, the output voltage goes above the regulation voltage. To regulate the output voltage, the TPP15052 goes into hiccup mode and stops switching for 500 μ s. After a 500- μ s hiccup, the TPP15052 resumes switching without a soft start.

Output Voltage Setting

The TPP15052 has preset 12-V, 15-V, and 18-V output voltage settings inside by connecting different resistances between the VSET pin and the ICGND pin, as shown in [Table 2](#).

Table 2. VOUT Setting by VSET Pin

VSET Connection	VOUT
VSET floating	12 V
VSET connected to ICGND	15 V
51-k Ω resistance between VSET and ICGND	18 V
150-k Ω resistance between VSET and ICGND	Adjustable VOUT set by an external resistor divider between VOUT and ICGND

When using an external resistor divider to set the output voltage, it is recommended using a resistor with a value less than 5 k Ω as the bottom resistor R_B between the FB pin and the ICGND pin. The upper resistor R_U between the FB pin and the output can be calculated by [Equation 1](#).

$$R_U = \left(\frac{V_{OUT} + V_F}{V_{REF}} - 1 \right) \times R_B \quad (1)$$

Where

- V_F is the forward voltage of the rectifier diode.
- V_{REF} is the internal reference voltage.

Dummy Load

A minimum load is needed to prevent the output voltage from running away to high voltage when the load current is too small. When the system is powered by the TPP15052, which may consume very small power in some conditions, like standby mode, a dummy load is needed. However, a large dummy load increases the power loss in the system standby condition. It is recommended using a 15-k Ω resistor at the output as the minimum load.

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode

Output Overload Protection

After startup, when the output voltage is below the regulation voltage, the output of the internal error amplifier goes up to the high limit and the switch current hits the limit. When the output voltage is below 90% of the target regulation voltage and the current limit is reached for 128 switching cycles, the TPP15052 enters hiccup mode and stops switching for 65 ms. After a 65-ms hiccup period, the TPP15052 restarts the soft startup. If the output voltage rises above 90% of the target regulation voltage within the 128 switching cycles, the overload timer resets.

Cycle-by-cycle Current Limit Protection

When the current through the power switch trips 1.5 A, the power switch is turned off immediately. The power switch is kept off until the next switching cycle.

Output Short-circuit Protection

When the output short-circuit happens, the current through the power switch goes up above the cycle-by-cycle limit because the inductor current continues to increase within the minimum on-time period of each cycle. When the TPP15052 detects the current through the power switch more than 2.2 A (50% higher than the limit), the TPP15052 goes into hiccup mode and stop switching for 65 ms. After a 65-ms hiccup period, the TPP15052 restarts soft start.

Thermal Shutdown Protection

A thermal shutdown is implemented to prevent damages due to excessive heat and power dissipation. Typically, the thermal shutdown happens at a junction temperature of 175°C. When the thermal shutdown is triggered, the device stops switching until the junction temperature falls below typically 150°C, then the device starts switching again.

Application and Implementation

Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Application Information

The TPP15052 is designed for outputting voltage from high input voltage up to 170 V. It adopts a peak current control scheme to achieve a fast transient response.

Typical Application

48-V input to 15-V output buck converter.




Figure 16. TPP15052 48-V to 15-V Buck Converter Application Circuit

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode

Application Examples

48-V input to 5-V output buck converter with the external voltage setting resistor divider.




Figure 17. TPP15052 48-V to 5-V Buck Converter Application Circuit

Layout

Layout Guideline

PCB layout is very critical for the performance of a DC to DC converter, especially for loop stability, EMI, and thermal performance. A good PCB layout with less parasitic inductance and capacitance results in a stable output voltage with less switching noise.

- Place the input bypass capacitor as close as possible to the VIN pin and the ground. Use short and wide trace to connect the input capacitor and the VIN pin. Care should be taken to minimize the loop area formed by the input bypass capacitor connections, the VIN pins, the ICGND pin, the external schottky diode and the ground connections.
- Since the ICGND connection is the switching node, the inductor should be located as close as possible to the ICGND pin. The area of the switching node connection must be kept small to minimize the EMI and the capacitive coupling between the ICGND node and the output.
- Use a low ESR ceramic capacitor as the boot capacitor between the VDD pin and the ICGND pin. The boot capacitor must also be located close to the VDD pin.
- When using an external resistor divider to set the output voltage, place the resistor divider as close as possible to the FB pin. The node of the center tap of the resistor divider and the FB pin must be kept far away from the ground plane to minimize the parasitic capacitance between the FB pin and ground.

Layout Example

Figure 18 and Figure 19 are two examples of PCB layout when using the TPP15052. For adjustable output voltage configuration, the node of the center tap of the feedback resistor divider and the FB pin must be kept far away from the ground plane to minimize the parasitic capacitance between the FB pin and ground.




Figure 18. PCB Layout Example for 15-V Fixed Output



170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode


Figure 19. PCB Layout Example for Adjustable Output


Tape and Reel Information



Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	W0 (mm)	Pin1 Quadrant
TPP15052-SO1R-C	SOP8	330	17.6	6.5	5.4	2	8	12	Q1

Package Outline Dimensions

SOP8



170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode**Order Information**

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPP15052-SO1R-C	-40 to 125°C	SOP8	15052	MSL3	Tape & Reel, 4000	Green

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

170-V, 0.5-A Asynchronous Buck Converter with Rectifier Diode

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2026. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.

This page intentionally left blank