

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Features

- 4-bit bidirectional Level Shift
- Open-Drain and Push-Pull Output
- Max Data Rate ($V_{CCA} = 3.3\text{ V}$ $V_{CCB} = 5\text{ V}$) :
 - 100 Mbps (Push-Pull), 1.2 Mbps (Open-drain)
- Voltage-Level Translation Between:
 - V_{CCA} Range 1.65 V to 3.6 V
 - V_{CCB} Range 1.65 V to 5.5 V
- 5 V Tolerant OE Enable Pin
- High-impedance A1~4 and B1~4 pins for OE = LOW
- VCC Isolation Feature: Either VCC Input = GND, All Outputs are in the High-Impedance State
- I_{OFF} supports partial Power-down mode
- No Power Up sequency required for V_{CCA} , V_{CCB}
- ESD Protection:
 - A Port $\pm 4000\text{-V}$ Human-Body Model
 - B Port $\pm 8000\text{-V}$ Human-Body Model
 - B Port $\pm 4000\text{-V}$ IEC 61000-4-2 Contact Discharge
 - 1500-V Charged-Device Model

Description

The TPT20104 device is a 4-bit level shifter, functions with an enable (OE) input and can work from 1.65 V to 3.6 V V_{CCA} and 1.65V to 5.5 V V_{CCB} . V_{CCA} must be less than or equal to V_{CCB} . TPT20104 support bidirectional voltage translation between 1.8 V, 2.5 V, 3.3 V and 5 V.

The A1~4 I/Os are connected to the B1~4 I/Os, which will allow bidirectional data flow between ports. If OE is low, the translator switch is off, and a high-impedance state exists between A ports and B ports to isolate both sides. And OE input circuit is internally connected to V_{CCA} .


4-bit bidirectional buffer isolates capacitance and allows 15 pF on either side of the device to support 100 Mbps speeds in Push-Pull mode in 3.3 V V_{CCA} and 5 V V_{CCB} supply, and support 1.2 Mbps speeds in Open-Drain mode.

TPT20104 is available in TSSOP14, QFN1.7x2.0-12, QFN3.5x3.5-14 package and is characterized from -40°C to $+125^{\circ}\text{C}$.

Applications

- Servers/Storages
- Routers (Telecom Switching Equipment)
- Personal Computers/Consumer handsets
- Industrial Automation

Functional Block Diagram



4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Table of Contents

Features.....	1
Applications.....	1
Description.....	1
Functional Block Diagram.....	1
Revision History.....	3
Pin Configuration and Functions.....	4
Specifications.....	6
Absolute Maximum Ratings ⁽¹⁾	6
ESD, Electrostatic Discharge Protection.....	6
Recommended Operating Conditions.....	7
Thermal Information.....	7
Electrical Characteristics.....	8
AC Timing Requirements -- VCCA = 1.8 V.....	10
AC Timing Requirements -- VCCA = 2.5 V.....	13
AC Timing Requirements -- VCCA = 3.3 V.....	15
Typical Performance Characteristics.....	17
Parameter Measurement Waveforms.....	18
Detailed Description.....	20
Overview.....	20
Functional Block Diagram.....	20
Feature Description.....	20
Application and Implementation.....	22
Application Information	22
Typical Application.....	22
Layout.....	23
Layout Example.....	23
Tape and Reel Information.....	24
Package Outline Dimensions.....	25
TSSOP14.....	25
QFN1.7X2-12-A.....	26
QFN3.5X3.5-14.....	27
Order Information.....	28
IMPORTANT NOTICE AND DISCLAIMER.....	29


4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull**Revision History**

Date	Revision	Notes
2024-07-19	Rev.Pre.0	Initial version
2024-08-28	Rev.A.0	Released version

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Pin Configuration and Functions

TPT20104-TS2R
TSSOP14 Package
Top View



TPT20104-QFMR
QFN3.5x3.5-14 Package
Top View




Table 1. Pin Functions: TPT20104

Pin		I/O	Description
No.	Name		
1	VCCA	I	side-A supply voltage
2	A1	I/O	Input/output A1. Referenced to V _{CCA}
3	A2	I/O	Input/output A2. Referenced to V _{CCA}
4	A3	I/O	Input/output A3. Referenced to V _{CCA}
5	A4	I/O	Input/output A4. Referenced to V _{CCA}
6	NC	--	No Connection
7	GND	I	Supply ground
8	OE	I	Active-high enable input, Referenced to V _{CCA}
9	NC	--	No Connection
10	B4	I/O	Input/output B4. Referenced to V _{CCB}
11	B3	I/O	Input/output B3. Referenced to V _{CCB}
12	B2	I/O	Input/output B2. Referenced to V _{CCB}
13	B1	I/O	Input/output B1. Referenced to V _{CCB}
14	VCCB	I	side-B supply voltage
15	Epad	--	For QFN package, the exposed thermal pad must be connected to ground

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

TPT20104-QN5R
QFN1.7x2-12 Package
Top View




Table 2. Pin Functions: TPT20104

Pin		I/O	Description
No.	Name		
1	VCCA	I	side-A supply voltage
2	A1	I/O	Input/output A1. Referenced to V _{CCA}
3	A2	I/O	Input/output A2. Referenced to V _{CCA}
4	A3	I/O	Input/output A3. Referenced to V _{CCA}
5	A4	I/O	Input/output A4. Referenced to V _{CCA}
6	GND	I	Supply ground
7	B4	I/O	Input/output B4. Referenced to V _{CCB}
8	B3	I/O	Input/output B3. Referenced to V _{CCB}
9	B2	I/O	Input/output B2. Referenced to V _{CCB}
10	B1	I/O	Input/output B1. Referenced to V _{CCB}
11	VCCB	I	side-B supply voltage
12	OE	i	Active-high enable input, Referenced to V _{CCA}

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Specifications

Absolute Maximum Ratings ⁽¹⁾

Parameter		Min	Max	Unit
V _{CCA}	DC reference voltage range (side-A)	-0.5	4.6	V
V _{CCB}	DC reference bias voltage range (side-B)	-0.5	6.5	V
V _I	Input voltage range, side-A	-0.5	4.6	V
	Input voltage range, side-B	-0.5	6.5	V
V _O	Voltage range applied to any output in the high-impedance or power-off state, V _O , side-A	-0.5	4.6	V
	Voltage range applied to any output in the high-impedance or power-off state, V _O , side-B	-0.5	6.5	V
	Voltage range applied to any output in the high or low state, V _O , side-A	-0.5	V _{CCA} +0.5	V
	Voltage range applied to any output in the high or low state, V _O , side-B	-0.5	V _{CCB} +0.5	V
I _{IK}	Input clamp current, V _I < 0		-50	mA
I _{OK}	Output clamp current, V _{I/O} < 0		-50	mA
I _O	Continuous output current	-50	50	mA
I _C	Continuous current through each V _{CCA} , V _{CCB} , or GND	-100	100	mA
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range	-65	150	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

(2) The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.

(3) The value of V_{CCA} and V_{CCB} are provided in the recommended operating conditions table.

ESD, Electrostatic Discharge Protection

Parameter		Condition	Value	Unit
HBM	Human Body Model ESD, side-A ports	ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	±4	kV
	Human Body Model ESD, side-B ports	ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	±8	kV
IEC ESD	IEC Contact Discharge	IEC-61000-4-2, Bus Pin: B ports	±4	kV
	IEC Air-Gap Discharge	IEC-61000-4-2, Bus Pin: B ports	±8	kV
CDM	Charged Device Model ESD, side-A and side-B ports	ANSI/ESDA/JEDEC JS-002 ⁽²⁾	±1.5	kV
LU	Latch up	LU, per JESD78, All Pin ⁽³⁾	±500	mA

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

(3) Test at the temperature of 25°C.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Recommended Operating Conditions

Parameter		V _{CCA}	V _{CCB}	Min	Max	Unit
V _{CCA}	Reference Voltage, side-A			1.65	3.6	V
V _{CCB}	Reference Voltage, side-B			1.65	5.5	V
V _{IH}	side-A ports High-level input voltage	1.65 V to 1.95 V	1.65 V to 5.5 V	V _{CCI} ⁽¹⁾ - 0.2	V _{CCI} ⁽¹⁾	V
	side-A ports High-level input voltage	2.3 V to 3.6 V	1.65 V to 5.5 V	V _{CCI} ⁽¹⁾ - 0.4	V _{CCI} ⁽¹⁾	V
	side-B ports High-level input voltage	1.65 V to 3.6 V	1.65 V to 5.5 V	V _{CCI} ⁽¹⁾ - 0.4	V _{CCI} ⁽¹⁾	V
	OE inputs High-level input voltage	1.65 V to 3.6 V	1.65 V to 5.5 V	V _{CCA} × 0.65	5.5	V
V _{IL}	side-A ports Low-level input voltage	1.65 V to 3.6 V	1.65 V to 5.5 V	0	0.15	V
	side-B ports Low-level input voltage	1.65 V to 3.6 V	1.65 V to 5.5 V	0	0.15	V
	OE inputs Low-level input voltage	1.65 V to 3.6 V	1.65 V to 5.5 V	0	V _{CCA} × 0.35	V
Δt/Δv	side-A ports Input transitionrise or fall rate	1.65 V to 3.6 V	1.65 V to 5.5 V		10	ns/V
	side-B ports Input transitionrise or fall rate	1.65 V to 3.6 V	1.65 V to 5.5 V		10	
	OE Input transitionrise or fall rate	1.65 V to 3.6 V	1.65 V to 5.5 V		10	
T _A	Operating Ambient Temperature			-40	125	°C

- (1) V_{CCI} is the supply voltage of the input side-A or side-B port.
(2) V_{CCO} is the supply voltage of the output side-A or side-B port.
(3) V_{CCA} should be less than or equal to V_{CCB}, and V_{CCA} must not high than 3.6 V.

Thermal Information

Package Type	θ _{JA}	θ _{JC}	Unit
TSSOP14	113	49	°C/W
QFN3.5x3.5-14	53	65	°C/W
QFN1.7x2-12	115	41	°C/W

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Electrical Characteristics

All test conditions: $V_{CCA} = 1.65\text{ V to }3.6\text{ V}$, $V_{CCB} = 1.65\text{ V to }5.5\text{ V}$, $GND = 0\text{ V}$, $T_A = -40^\circ\text{C to }+125^\circ\text{C}$, unless otherwise noted.

Parameter	Conditions	V_{CCA}	V_{CCB}	Min	Typ	Max	Unit
Supply Voltage and Current							
V_{OHA}	Port A High-level Output voltage	$I_{OH} = -20\text{ }\mu\text{A}$, $V_{IB} \geq V_{CCB} - 0.4\text{ V}$	1.65 V to 3.6 V	1.65 V to 5.5 V	$V_{CCA} \times 0.67$		V
V_{OLA}	Port A Low-level Output Voltage	$I_{OL} = 220\text{ }\mu\text{A}$, $V_{IB} \leq 0.15\text{ V}$	1.65 V	1.65 V to 5.5 V		0.4	V
		$I_{OL} = 300\text{ }\mu\text{A}$, $V_{IB} \leq 0.15\text{ V}$	2.3 V	1.65 V to 5.5 V		0.4	
		$I_{OL} = 400\text{ }\mu\text{A}$, $V_{IB} \leq 0.15\text{ V}$	3.0 V	3.0 V to 5.5 V		0.55	
		$I_{OL} = 1000\text{ }\mu\text{A}$, $V_{IB} \leq 0.15\text{ V}$	1.65 V to 3.6 V	3.0 V to 5.5 V		0.6	
V_{OHB}	Port B High-level Output voltage	$I_{OH} = -20\text{ }\mu\text{A}$, $V_{IA} \geq V_{CCA} - 0.2\text{ V}$	1.65 V to 3.6 V	1.65 V to 5.5 V	$V_{CCB} \times 0.67$		V
V_{OLB}	Port B Low-level Output voltage	$I_{OL} = 220\text{ }\mu\text{A}$, $V_{IA} \leq 0.15\text{ V}$	1.65 V to 3.6 V	1.65 V		0.4	V
		$I_{OL} = 300\text{ }\mu\text{A}$, $V_{IA} \leq 0.15\text{ V}$	1.65 V to 3.6 V	2.3 V		0.4	
		$I_{OL} = 400\text{ }\mu\text{A}$, $V_{IA} \leq 0.15\text{ V}$	1.65 V to 3.6 V	3.0 V		0.55	
		$I_{OL} = 620\text{ }\mu\text{A}$, $V_{IA} \leq 0.15\text{ V}$	1.65 V to 3.6 V	4.5 V		0.55	
		$I_{OL} = 1000\text{ }\mu\text{A}$, $V_{IA} \leq 0.15\text{ V}$	1.65 V to 3.6 V	4.5 V		0.6	
I_I	Input leakage current	OE: $V_I = V_{CCI}$ or GND	1.65 V	1.65 V to 5.5 V	-2	2	μA
I_{OZ}	Highimpedance state output current	Port A or B, OE = GND	1.65 V	1.65 V to 5.5 V	-2	2	μA
I_{CCA}	Quiescent Supply Current for V_{CCA}	$V_I = V_O = \text{Open}$, $I_O = 0$, OE = V_{CCA}	1.65 V to 3.6 V	1.65 V to 5.5 V		5	μA
			3.6 V	0		5	
			0	5.5 V	-1	1	
I_{CCB}	Quiescent Supply Current for V_{CCB}	$V_I = V_O = \text{Open}$, $I_O = 0$, OE = V_{CCA}	1.65 V to 3.6 V	1.65 V to 5.5 V		15	μA
			3.6 V	0	-1	1	
			0	5.5 V		10	

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Parameter		Conditions	V _{CCA}	V _{CCB}	Min	Typ	Max	Unit
I _{CCA} + I _{CCB}	Combined supply current	V _I = V _{CCI} , I _O = 0, OE = V _{CCA}	1.65 V to 3.6 V	1.65 V to 5.5 V			15	μA
I _{OFF}	OFF current	A port: V _I or V _O = 0 to 3.6	0	0 V to 5.5 V	-5		5	μA
		B port: V _I or V _O = 0 to 3.6	0 V to 3.6 V	0	-5		5	μA
I _{CCZA}	High impedance state V _{CCA} supply current	V _I = V _O = Open, I _O = 0, OE = GND	1.65 V to 3.6 V	1.65 V to 5.5 V			5	μA
I _{CCZB}	High impedance state V _{CCB} supply current	V _I = V _O = Open, I _O = 0, OE = GND	1.65 V to 3.6 V	1.65 V to 5.5 V			15	μA
C _I	Input Capacitance ⁽¹⁾	OE	3.3 V	3.3 V		5	10	pF
C _{IO}	Input/output Capacitance ⁽¹⁾	Port A	3.3 V	3.3 V		7	10	pF
		Port B	3.3 V	3.3 V		10	15	pF

(1) Test data based on bench tests and design simulation, NOT test in production.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

AC Timing Requirements -- VCCA = 1.8 V

All test conditions: V_{CCA} = 1.65 V to 1.95 V, GND = 0 V, T_A = -40°C to +125°C, unless otherwise noted.

Parameter	Condition	V _{CCB}	Min	Typ	Max	Unit
f _D ⁽¹⁾	Data rate	Push-pull mode	1.65 V to 1.95 V		40	Mbps
			2.3 V to 2.7 V		45	Mbps
			3.0 V to 3.6 V		40	Mbps
			4.5 V to 5.5 V		40	Mbps
		Open-drain mode	1.65 V to 1.95 V		0.8	Mbps
			2.3 V to 2.7 V		0.8	Mbps
			3.0 V to 3.6 V		0.8	Mbps
			4.5 V to 5.5 V		1	Mbps
t _w ⁽¹⁾	Pulse duration	Push-pull mode	1.65 V to 1.95 V	25		ns
			2.3 V to 2.7 V	22.22		ns
			3.0 V to 3.6 V	25		ns
			4.5 V to 5.5 V	25		ns
		Open-drain mode	1.65 V to 1.95 V	1250		ns
			2.3 V to 2.7 V	1250		ns
			3.0 V to 3.6 V	1250		ns
			4.5 V to 5.5 V	1000		ns
t _{PHL} ⁽¹⁾	Propagation Delay (High-to-Low)	A-to-B, push-pull driving	1.65 V to 1.95 V		20	ns
			2.3 V to 2.7 V		20	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns
		A-to-B, open-drain driving	1.65 V to 1.95 V	1.7	20	ns
			2.3 V to 2.7 V	1.7	20	ns
			3.0 V to 3.6 V	1.6	15	ns
			4.5 V to 5.5 V	1.5	15	ns
t _{PLH} ⁽¹⁾	Propagation Delay (Low-to-High)	A-to-B, push-pull driving	1.65 V to 1.95 V		20	ns
			2.3 V to 2.7 V		20	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Parameter	Condition	V _{CCB}	Min	Typ	Max	Unit
	A-to-B, open-drain driving	1.65 V to 1.95 V			800	ns
		2.3 V to 2.7 V			700	ns
		3.0 V to 3.6 V			600	ns
		4.5 V to 5.5 V			500	ns
t _{PHL} ⁽¹⁾	B-to-A, push-pull driving	1.65 V to 1.95 V			20	ns
		2.3 V to 2.7 V			17	ns
		3.0 V to 3.6 V			15	ns
		4.5 V to 5.5 V			15	ns
	B-to-A, open-drain driving	1.65 V to 1.95 V			20	ns
		2.3 V to 2.7 V	2		20	ns
		3.0 V to 3.6 V	1.9		15	ns
		4.5 V to 5.5 V	1.8		15	ns
t _{PLH} ⁽¹⁾	B-to-A, push-pull driving	1.65 V to 1.95 V			20	ns
		2.3 V to 2.7 V			15	ns
		3.0 V to 3.6 V			15	ns
		4.5 V to 5.5 V			15	ns
	B-to-A, open-drain driving	1.65 V to 1.95 V			900	ns
		2.3 V to 2.7 V			700	ns
		3.0 V to 3.6 V			600	ns
		4.5 V to 5.5 V			500	ns
t _{en} ⁽¹⁾	Enable time	OE-to-A or B, push-pull driving	1.65 V to 5.5 V		100	ns
t _{dis} ⁽¹⁾	Disable time	OE-to-A or B, push-pull driving	1.65 V to 5.5 V		410	ns
tr _A ⁽¹⁾	Input rise time	A-port rise time, push-pull driving	1.65 V to 1.95 V		20	ns
			2.3 V to 2.7 V	1.6	20	ns
			3.0 V to 3.6 V	1.4	15	ns
			4.5 V to 5.5 V	1.4	15	ns
	A-port rise time, open-drain driving	1.65 V to 1.95 V	1.7		1200	ns
		2.3 V to 2.7 V	1.7		800	ns

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Parameter	Condition	V _{CCB}	Min	Typ	Max	Unit
		3.0 V to 3.6 V	1.4		600	ns
		4.5 V to 5.5 V	1.2		500	ns
tr _B ⁽¹⁾	Input rise time	B-port rise time, push-pull driving	1.65 V to 1.95 V	1.3	22	ns
			2.3 V to 2.7 V	1.3	20	ns
			3.0 V to 3.6 V	0.9	15	ns
			4.5 V to 5.5 V	0.7	15	ns
		B-port rise time, open-drain driving	1.65 V to 1.95 V	1	1200	ns
			2.3 V to 2.7 V	1	800	ns
			3.0 V to 3.6 V	1	700	ns
			4.5 V to 5.5 V	0.6	500	ns
tf _A ⁽¹⁾	Input fall time	A-port fall time, push-pull driving	1.65 V to 1.95 V	1	20	ns
			2.3 V to 2.7 V	1.6	20	ns
			3.0 V to 3.6 V	1.4	15	ns
			4.5 V to 5.5 V	1.4	15	ns
		A-port fall time, open-drain driving	1.65 V to 1.95 V	1.7	20	ns
			2.3 V to 2.7 V	1.7	15	ns
			3.0 V to 3.6 V	1.4	15	ns
			4.5 V to 5.5 V	1.2	15	ns
tf _B ⁽¹⁾	Input fall time	B-port fall time, push-pull driving	1.65 V to 1.95 V	1.3	20	ns
			2.3 V to 2.7 V	1.3	15	ns
			3.0 V to 3.6 V	0.9	10	ns
			4.5 V to 5.5 V	0.7	10	ns
		B-port fall time, open-drain driving	1.65 V to 1.95 V	1	20	ns
			2.3 V to 2.7 V	1	20	ns
			3.0 V to 3.6 V	1	15	ns
			4.5 V to 5.5 V	0.7	15	ns
t _{SK(O)} ⁽¹⁾	Skew (time), output	Channel-to channel skew, push-pull driving	1.65 V to 5.5 V		1	ns

(1) The data is based on bench test and design simulation, Not test in production.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

AC Timing Requirements -- VCCA = 2.5 V

All test conditions: VCCA = 2.3 V to 2.7 V, GND = 0 V, TA = -40°C to +125°C, unless otherwise noted.

Parameter	Condition	VCCB	Min	Typ	Max	Unit
f _D ⁽¹⁾	Data rate	Push-pull mode	2.3 V to 2.7 V		60	Mbps
			3.0 V to 3.6 V		75	Mbps
			4.5 V to 5.5 V		75	Mbps
		Open-drain mode	2.3 V to 2.7 V		0.8	Mbps
			3.0 V to 3.6 V		0.8	Mbps
			4.5 V to 5.5 V		1	Mbps
t _W ⁽¹⁾	Pulse duration	Push-pull mode	2.3 V to 2.7 V	16.66		ns
			3.0 V to 3.6 V	13.33		ns
			4.5 V to 5.5 V	13.33		ns
		Open-drain mode	2.3 V to 2.7 V	1250		ns
			3.0 V to 3.6 V	1250		ns
			4.5 V to 5.5 V	1000		ns
t _{PHL} ⁽¹⁾	Propagation Delay (High-to-Low)	A-to-B, push-pull driving	2.3 V to 2.7 V		15	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns
		A-to-B, open-drain driving	2.3 V to 2.7 V		15	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns
t _{PLH} ⁽¹⁾	Propagation Delay (Low-to-High)	A-to-B, push-pull driving	2.3 V to 2.7 V		15	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns
		A-to-B, open-drain driving	2.3 V to 2.7 V		15	ns
			3.0 V to 3.6 V		30	ns
			4.5 V to 5.5 V		20	ns
t _{PHL} ⁽¹⁾	Propagation Delay (High-to-Low)	B-to-A, push-pull driving	2.3 V to 2.7 V		15	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns
		B-to-A, open-drain driving	2.3 V to 2.7 V		15	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns
t _{PLH} ⁽¹⁾	Propagation Delay (Low-to-High)	B-to-A, push-pull driving	2.3 V to 2.7 V		15	ns
			3.0 V to 3.6 V		15	ns
			4.5 V to 5.5 V		15	ns

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Parameter	Condition	VCCB	Min	Typ	Max	Unit
	B-to-A, open-drain driving	2.3 V to 2.7 V			15	ns
		3.0 V to 3.6 V			10	ns
		4.5 V to 5.5 V			10	ns
$t_{en}^{(1)}$	Enable time	OE-to-A or B, push-pull driving	2.3 V to 5.5 V		100	ns
$t_{dis}^{(1)}$	Disable time	OE-to-A or B, push-pull driving	2.3 V to 5.5 V		400	ns
$tr_A^{(1)}$	Input rise time	A-port rise time, push-pull driving	2.3 V to 2.7 V	1.89	15	ns
			3.0 V to 3.6 V	1.6	15	ns
			4.5 V to 5.5 V	1.5	15	ns
		A-port rise time, open-drain driving	2.3 V to 2.7 V	110	800	ns
			3.0 V to 3.6 V	157	700	ns
			4.5 V to 5.5 V	116	500	ns
$tr_B^{(1)}$	Input rise time	B-port rise time, push-pull driving	2.3 V to 2.7 V	1.7	15	ns
			3.0 V to 3.6 V	1.3	10	ns
			4.5 V to 5.5 V	0.9	10	ns
		B-port rise time, open-drain driving	2.3 V to 2.7 V	107	800	ns
			3.0 V to 3.6 V	140	600	ns
			4.5 V to 5.5 V	77	500	ns
$tf_A^{(1)}$	Input fall time	A-port fall time, push-pull driving	2.3 V to 2.7 V	1.5	10	ns
			3.0 V to 3.6 V	1.2	10	ns
			4.5 V to 5.5 V	1.3	10	ns
		A-port fall time, open-drain driving	2.3 V to 2.7 V	1.5	10	ns
			3.0 V to 3.6 V	1.2	10	ns
			4.5 V to 5.5 V	1.1	10	ns
$tf_B^{(1)}$	Input fall time	B-port fall time, push-pull driving	2.3 V to 2.7 V	1.4	10	ns
			3.0 V to 3.6 V	0.9	10	ns
			4.5 V to 5.5 V	0.7	10	ns
		B-port fall time, open-drain driving	2.3 V to 2.7 V	0.4	20	ns
			3.0 V to 3.6 V	0.5	10	ns
			4.5 V to 5.5 V	0.4	10	ns
$t_{sk(O)}^{(1)}$	Skew (time), output	Channel-to channel skew, push-pull driving	2.3 V to 5.5 V		1	ns

(1) The data is based on bench test and design simulation, Not test in production.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

AC Timing Requirements -- VCCA = 3.3 V

All test conditions: V_{CCA} = 3.0 V to 3.6 V, GND = 0 V, T_A = -40°C to +125°C, unless otherwise noted.

Parameter	Condition	V _{CCB}	Min	Typ	Max	Unit
f _D ⁽¹⁾	Data rate	Push-pull mode	3.0 V to 3.6 V		80	Mbps
		Push-pull mode	4.5 V to 5.5 V		100	Mbps
		Open-drain mode	3.0 V to 3.6 V		0.8	Mbps
		Open-drain mode	4.5 V to 5.5 V		1.2	Mbps
t _w ⁽¹⁾	Pulse duration	Push-pull mode	3.0 V to 3.6 V	12.5		ns
		Push-pull mode	4.5 V to 5.5 V	10		ns
		Open-drain mode	3.0 V to 3.6 V	1250		ns
		Open-drain mode	4.5 V to 5.5 V	833		ns
t _{PHL} ⁽¹⁾	Propagation Delay (High-to-Low)	A-to-B, push-pull driving	3.0 V to 3.6 V		15	ns
		A-to-B, push-pull driving	4.5 V to 5.5 V		10	ns
		A-to-B, open-drain driving	3.0 V to 3.6 V	2.1	20	ns
		A-to-B, open-drain driving	4.5 V to 5.5 V	1.5	15	ns
t _{PLH} ⁽¹⁾	Propagation Delay (Low-to-High)	A-to-B, push-pull driving	3.0 V to 3.6 V		15	ns
		A-to-B, push-pull driving	4.5 V to 5.5 V		15	ns
		A-to-B, open-drain driving	3.0 V to 3.6 V	0.15	900	ns
		A-to-B, open-drain driving	4.5 V to 5.5 V	0.3	500	ns
t _{PHL} ⁽¹⁾	Propagation Delay (High-to-Low)	B-to-A, push-pull driving	3.0 V to 3.6 V		15	ns
		B-to-A, push-pull driving	4.5 V to 5.5 V		15	ns
		B-to-A, open-drain driving	3.0 V to 3.6 V	3.19	20	ns
		B-to-A, open-drain driving	4.5 V to 5.5 V	1.8	15	ns
t _{PLH} ⁽¹⁾	Propagation Delay (Low-to-High)	B-to-A, push-pull driving	3.0 V to 3.6 V		20	ns
		B-to-A, push-pull driving	4.5 V to 5.5 V		10	ns
		B-to-A, open-drain driving	3.0 V to 3.6 V		900	ns
		B-to-A, open-drain driving	4.5 V to 5.5 V		500	ns
t _{en} ⁽¹⁾	Enable time	OE-to-A or B, push-pull driving	3.0 V to 5.5 V		100	ns

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Parameter		Condition	V _{CCB}	Min	Typ	Max	Unit
$t_{dis}^{(1)}$	Disable time	OE-to-A or B, push-pull driving	3.0 V to 3.6 V			410	ns
$tr_A^{(1)}$	Input rise time	A-port rise time, push-pull driving	3.0 V to 3.6 V	2.1		15	ns
			4.5 V to 5.5 V	1.4		15	ns
		A-port rise time, open-drain driving	3.0 V to 3.6 V	2.2		446	ns
			4.5 V to 5.5 V	1.2		337	ns
$tr_B^{(1)}$	Input rise time	B-port rise time, push-pull driving	3.0 V to 3.6 V	2		15	ns
			4.5 V to 5.5 V	0.7		10	ns
		B-port rise time, open-drain driving	3.0 V to 3.6 V	2		427	ns
			4.5 V to 5.5 V	0.6		290	ns
$tf_A^{(1)}$	Input fall time	A-port fall time, push-pull driving	3.0 V to 3.6 V	1.4		10	ns
			4.5 V to 5.5 V	1.2		10	ns
		A-port fall time, open-drain driving	3.0 V to 3.6 V	1.4		10	ns
			4.5 V to 5.5 V	1.2		10	ns
$tf_B^{(1)}$	Input fall time	B-port fall time, push-pull driving	3.0 V to 3.6 V	1.3		10	ns
			4.5 V to 5.5 V	1.1		10	ns
		B-port fall time, open-drain driving	3.0 V to 3.6 V	1.3		10	ns
			4.5 V to 5.5 V	1.1		10	ns
$t_{SK(O)}^{(1)}$	Skew (time), output	Channel-tochannel skew, push-pull driving	3.0 V to 5.5 V			1	ns

(1) The data is based on bench test and design simulation ,Not test in production.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Typical Performance Characteristics

All test conditions: $V_{CCA} = 1.65\text{ V}$ to 3.6 V $V_{CCB} = 1.65\text{ V}$ to 5.5 V , unless otherwise noted.




Figure 1. $V_{CCA} = 1.8\text{ V}$ $V_{OL(Ax)}$ vs $I_{OL(Ax)}$




Figure 2. $V_{CCA} = 2.5\text{ V}$ $V_{OL(Ax)}$ vs $I_{OL(Ax)}$




Figure 3. $V_{CCA} = 3.3\text{ V}$ $V_{OL(Ax)}$ vs $I_{OL(Ax)}$

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Parameter Measurement Waveforms




Figure 4. Timing Measurement Load Circuit of Push-Pull Driver




Figure 5. Timing Measurement Load Circuit of Push-Pull Driver

Test	S1
t_{PZL}/t_{PLZ}	$2 \times V_{CCO}$
t_{PHZ}/t_{PZH}	Open




Figure 6. Load Circuit for Enable and Disable Time measurement




Figure 7. Pulse Duration




Figure 8. Propagation Delay Times

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull




Figure 9. Enable and Disable Times

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Detailed Description

Overview

The TPT20104 device is a 4-bit level shifter, functions with an enable (OE) input and can work from 1.65 V to 3.6 V V_{CCA} and 1.65 V to 5.5 V V_{CCB} . V_{CCA} must be less than or equal to V_{CCB} . TPT20104 support bidirectional voltage translation between 1.8 V, 2.5 V, 3.3 V and 5 V. The A1~4 I/O are connected to the B1~4 I/O, which will allow bidirectional data flow between ports. If OE is low, the translator switch is off, and a high-impedance state exists between ports to isolate both sides. And OE input circuit is internally connected to V_{CCA} . 4-bit bidirectional buffer isolates capacitance and allows 15 pF on either side of the device to support 100 Mbps speeds in Push-Pull mode in 3.3 V V_{CCA} and 5 V V_{CCB} , and support 1.2Mbps speed in Open-Drain mode.

Functional Block Diagram




Figure 10. Functional Block Diagram

Feature Description

Power Up

During operation, to make sure that $V_{CCA} \leq V_{CCB}$ at all times. During power-up period, even $V_{CCA} \geq V_{CCB}$, it does not damage the device, so there is no power on sequence requirement, any power supply can be ramped up first.

Enable (OE)

The TPT20104 device has two functional modes, enabled and disabled. To disable the device setting the OE input as LOW level, which places all I/Os in a high impedance state. Setting the OE input as HIGH level will enable the device.

The OE pin is active HIGH with thresholds referenced to V_{CCA} and an internal pull-up to V_{CCA} that maintains the device active, unless the user selects to disable the TPT20104 when set OE low to place all I/Os in high impedance state. The t_{dis} parameter indicates the delay time between OE pin going low and I/Os outputs entering the high impedance state. Then Enable time t_{en} indicates the period time that user operates the one-shot circuit after OE pin is going high.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull**Table 3. Device Function table**

Input OE ⁽¹⁾	Translator Function
H	Ax = Bx
L	Ax is disconnected to Bx, high impedance

(1) OE = Floating, the I/O goes Hi-Z

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Application and Implementation

Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Application Information

The TPT20104 device is a 4-bit level shifter, functions with an enable (OE) input, and can work from 1.65 V to 3.6 V V_{CCA} and 1.65V to 5.5 V V_{CCB} . V_{CCA} must be less than or equal to V_{CCB} . TPT20104 supports bidirectional voltage translation between 1.8 V, 2.5 V, 3.3 V and 5 V. The A1~4 I/O are connected to the B1~4 I/O, which will allow bidirectional data flow between ports. If EN is low, the translator switch is off, and a high-impedance state exists between ports to isolate both sides. And OE input circuit is internally connected to V_{CCA} .

- Servers/Storages
- Routers (Telecom Switching Equipment)
- Personal Computers/Consumer handsets
- Industrial Automation

Typical Application

A typical application is shown in [Figure 11](#). The TPT20104 device can be used in level-translation applications for interfacing devices or systems operating at different interface voltages with one another. The TPT20104 device is ideal for use in applications where an open-drain driver is connected to the data I/Os, and also can be used in applications where a push-pull driver is connected to the data I/Os.




Figure 11. Typical Application Circuit

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Layout

Layout Example

Reflections and matching are closely related to loop antenna theory, but different enough to warrant their own discussion. When a PCB trace turns a corner at a 90° angle, a reflection can occur. This is primarily due to the change in width of the trace. At the apex of the turn, the trace width is increased to 1.414 times its width. This change in width upsets the transmission line characteristics, especially the distributed capacitance and self-inductance of the trace, thus resulting in the reflection. Not all PCB traces can be straight, so they will have to turn corners. Below shows progressively better techniques of rounding corners. Only the last example (BEST) maintains constant trace width and minimizes reflections.




Figure 12. Trace Example

Route high-speed signals using a minimum of vias and corners which reduces signal reflections and impedance changes. When a via must be used, increase the clearance size around it to minimize its capacitance. Each via introduces discontinuities in the signal's transmission line and increases the chance of picking up interference from the other layers of the board. Be careful when designing test points, through-hole pins are not recommended at high frequency.





Figure 13. Layout Example

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Tape and Reel Information







Order Number	Package	D1 (mm)	A0 (mm)	K0 (mm)	W0 (mm)	W1 (mm)	B0 (mm)	P0 (mm)	Pin1 Quadrant
TPT20104-TS2R	TSSOP14	330.0	6.8	1.5	12.0	17.6	5.5	8.0	Q1
TPT20104-QFMR	QFN3.5X3.5-14	330.0	3.8	1.1	12.0	17.6	3.8	8.0	Q1
TPT20104-QN5R	QFN1.7X2-12	180.0	1.9	0.75	8.0	13.1	2.3	4.0	Q1

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

Package Outline Dimensions

TSSOP14



4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull
QFN1.7X2-12-A
Package Outline Dimensions
QN5(QFN1.7X2-12-A)

TOP VIEW

SIDE VIEW

BOTTOM VIEW
NOTES





1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.450	0.550	0.018	0.022
A1	0.000	0.050	0.000	0.002
A3	0.152 REF		0.006 REF	
b	0.150	0.250	0.006	0.010
b1	0.150 REF		0.006 REF	
D	1.600	1.800	0.063	0.071
E	1.900	2.100	0.075	0.083
e	0.400 BSC		0.016 BSC	
L	0.400	0.600	0.016	0.024

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

QFN3.5X3.5-14

Package Outline Dimensions

QFM(QFN3.5X3.5-14-A)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.850	0.950	0.033	0.039
A1	0.000	0.050	0.000	0.002
b	0.200	0.300	0.008	0.012
b1	0.180 REF		0.007 REF	
c	0.203 REF		0.008 REF	
D	3.400	3.600	0.134	0.142
D2	1.950	2.150	0.077	0.085
D3	0.100	0.300	0.004	0.012
D4	0.040	0.240	0.002	0.009
E	3.400	3.600	0.134	0.142
E2	1.950	2.150	0.077	0.085
E3	2.600	2.800	0.102	0.110
e	0.500 BSC		0.020 BSC	
e1	0.750 BSC		0.030 BSC	
e2	0.275 BSC		0.011 BSC	
L	0.350	0.450	0.014	0.018
h	0.250	0.350	0.010	0.014

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.
3. The many types of E-pad Pin1 signs may appear in the product.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull**Order Information**

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPT20104-QFMR	-40 to 125°C	QFN3.5X3.5-14	20104	MSL3	Tape and Reel,4000	Green
TPT20104-QN5R	-40 to 125°C	QFN1.7X2-12	T14	MSL1	Tape and Reel,4000	Green
TPT20104-TS2R	-40 to 125°C	TSSOP-14	20104	MSL3	Tape and Reel,3000	Green

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

4-bit Bidirectional Level Shifter for Open-Drain and Push-Pull

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2024. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.

This page intentionally left blank