

Features

- Exceeds Requirements of EIA-485 Standard
- Data Rate: 20 Mbps or 500 Kbps
- Up to 256 Nodes on a Bus (1/8 Unit Load)
- Full Fail-Safe Receiver (Open, Short, and Terminated)
- Wide Supply Voltage Range: 3 V to 5.5 V
- 1.65 V to V_{CC} Supply for Digital IOs
- Bus-Pin Protection:
 - ± 18 -kV HBM ESD
 - ± 15 -kV IEC61000-4-2 Contact Discharge
 - ± 15 -kV IEC61000-4-2 Air Discharge

Description

The TPT4181V/H is a 3.0-V to 5.5-V, IEC electrostatic discharge (ESD) protected RS-485 transceiver. The device supports ± 15 -kV Contact Discharge on the transceiver bus pins without damage. The TPT4181V/H features a V_{IO} logic supply pin allowing a flexible digital interface capable of operating as low as 1.65 V.

Transmitters in this family deliver exceptional differential output voltages into the RS-485 required 54- Ω loads. Receiver (Rx) inputs feature a "Full Fail-Safe" design, which ensures a logic-high Rx output if Rx inputs are floating, shorted, or on a terminated but undriven bus.

The TPT4181V/H is available in the SOP8 package and is characterized from -40°C to 125°C .

Applications

- Factory Automation
- Field Bus Networks
- Industrial/Process Control Networks
- Communication Infrastructure

Typical RS-485 Network




Table of Contents

Features	1
Applications	1
Description	1
Typical RS-485 Network	1
Product Family Table	3
Revision History	3
Pin Configuration and Functions	4
Specifications	5
Absolute Maximum Ratings ⁽¹⁾	5
ESD, Electrostatic Discharge Protection.....	5
Recommended Operating Conditions.....	5
Thermal Information.....	6
Electrical Characteristics.....	7
Test Circuits and Waveforms.....	10
Tape and Reel Information	14
Package Outline Dimensions	15
SOP8.....	15
Order Information	16
IMPORTANT NOTICE AND DISCLAIMER	17

Product Family Table

Device	Data Rate	Package
TPT4181V	500K bps	SOP8
TPT4181H	20M bps	SOP8

Revision History

Date	Revision	Notes
2025-08-19	Rev.A.0	Released version

Pin Configuration and Functions




Table 1. Pin Functions

Pin No.	Name	I/O	Description
1	V _{IO}	Logic Supply	1.65-V to V _{CC} supply for logic I/O signals R, D, DE/ \overline{RE} .
2	R	Digital Output	Receive data output.
3	DE/ \overline{RE}	Digital Input	Driver/Receiver enable input. Driver enable (Active high), Receiver enable (Active Low).
4	D	Digital Input	Transmission data input
5	GND	Reference Potential	Local device ground.
6	A	Bus I/O	Digital bus I/O, A.
7	B	Bus I/O	Digital bus I/O, B.
8	V _{CC}	Bus Supply	3-V to 5.5-V supply for A and B bus lines.

Specifications

Absolute Maximum Ratings ⁽¹⁾

Parameter		Min	Max	Unit
V _{IO} to GND		-0.3	7	V
V _{CC} to GND		-0.3	7	V
Voltage at Logic Pin: DI, DE/ \overline{RE} , R		-0.3	V _{CC} + 0.3	V
Voltage at Bus Pin: A, B		-15	+15	V
T _A	Operating Temperature Range	-40	125	°C
T _{STG}	Storage Temperature Range	-65	150	°C
T _J	Maximum Junction Temperature		150	°C
T _L	Lead Temperature (Soldering, 10 sec)		260	°C

(1) Stresses beyond the *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*.

ESD, Electrostatic Discharge Protection

Symbol	Parameter	Condition	Minimum Level	Unit
	IEC-61000-4-2, Contact Discharge	Bus Pin	±15	kV
	IEC-61000-4-2, Air-Gap Discharge	Bus Pin	±15	kV
HBM	per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾ / ANSI/ESD STM5.5.1	Bus Pin	±18	kV
		All Pin except Bus Pin	±4	kV
CDM	per ANSI/ESDA/JEDEC JS-002 ⁽²⁾	All Pin	±1	kV

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

Recommended Operating Conditions

Parameter		Min	Typ	Max	Unit
V _{IO}		1.65		V _{CC}	V
V _{CC}		3		5.5	V
Voltage at Logic Pin: DI, DE/ \overline{RE} , R				V _{IO}	V
Voltage at Bus Pin: A, B		-7		+12	V
Operating Temperature Range		-40		125	°C

Thermal Information

Package Type	θ_{JA}	θ_{JC}	Unit
SOP8	120	60	°C/W

Electrical Characteristics

All test conditions: $V_{CC} = 3.3\text{ V to }5.0\text{ V}$, $T_A = -40^\circ\text{C to }125^\circ\text{C}$, unless otherwise noted.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V _{OD}	Driver Differential Output Voltage Magnitude	R _L = 60 Ω, 375 Ω on A/B: -7 V to 12 V, V _{CC} = 3.3 V	1.5	1.9		V
		R _L = 60 Ω, 375 Ω on A/B: -7 V to 12 V, V _{CC} = 5 V	2.0	3.0		V
		R _L = 54 Ω, V _{CC} = 3.3 V	1.5	2.0		V
		R _L = 54 Ω, V _{CC} = 5.0 V	2.0	3.0		V
		R _L = 100 Ω, V _{CC} = 3.3 V	1.5	2.3		V
		R _L = 100 Ω, V _{CC} = 5.0 V	2.0	3.5		V
Δ V _{OD}	Change in Magnitude of Driver Differential Output Voltage	R _L = 54 Ω, C _L = 50 pF, 375 Ω on A/B: -7 V to 12 V, V _{CC} = 3.3 V	-50		50	mV
V _{OC(SS)}	Steady-State Common-Mode Output Voltage	Center of two 27-Ω load resistors	1	V _{CC} / 2	3	V
ΔV _{OC}	Change in Differential Driver Output Common-Mode Voltage		-50		50	mV
V _{OC(PP)}	Peak-to-Peak Driver Common-Mode Output Voltage ⁽¹⁾			500		mV
C _{OD}	Differential Output Capacitance ⁽¹⁾			15		pF
V _{IT+}	Positive-Going Receiver Differential Input Voltage Threshold			-100	-20	mV
V _{IT-}	Negative-Going Receiver Differential Input Voltage Threshold		-220	-150		mV
V _{HYS}	Receiver Differential Input Voltage Threshold Hysteresis (V _{IT+} - V _{IT-}) ⁽¹⁾			50		mV
V _{OH}	Receiver High-Level Output Voltage	V _{IO} = 1.65 V, I _{OH} = -2 mA	1.3	1.5		V
		V _{IO} = 3 V, I _{OH} = -2 mA	2.8	2.9		
V _{OL}	Receiver Low-Level Output Voltage	V _{IO} = 1.65 V, I _{OL} = 2 mA		0.13	0.35	V
		V _{IO} = 3 V, I _{OL} = 2 mA		0.07	0.2	
V _{IH}	Input High Logic Level	D, DE/ $\overline{\text{RE}}$	2/3 V _{IO}			V
V _{IL}	Input Low Logic Level	D, DE/ $\overline{\text{RE}}$			1/3 V _{IO}	V
I _{IN}	Driver Input, Driver Enable, and Receiver Enable Input Current	D, DE/ $\overline{\text{RE}}$	-5		5	μA
I _{OZ}	Receiver Output High-Z Current	V _O = 0 V or V _{IO} , RE at V _{IO}	-1		1	μA

3.0-V to 5.5-V RS-485 Transceivers with 1.8-V I/O

Symbol	Parameter	Conditions	Min	Typ	Max	Unit	
I _{OS}	Driver Short-Circuit Output Current	V _A , V _B = -7 V to 12 V	-250		250	mA	
		A, B short	-120		120	mA	
I _{IA/B}	Bus Input Current (Disabled Driver)	V _{IO} = 1.8 V, DE at 0 V V _{CC} = 5.0 V, or V _{CC} = 0 V	V _I = 12 V		100	150	μA
			V _I = -7 V	-100	-50		μA
I _{CC}	Supply Current (Quiescent), TPT4181H	Driver enabled, receiver disabled	DE/ \overline{RE} = V _{CC} , no load		450	560	μA
		Driver disabled, receiver enabled	DE/ \overline{RE} = GND, no load		1600	2000	μA
I _{CC}	Supply Current (Quiescent), TPT4181V	Driver enabled, receiver disabled	DE/ \overline{RE} = V _{CC} , no load		400	600	μA
		Driver disabled, receiver enabled	DE/ \overline{RE} = GND, no load		400	600	μA

(1) Parameters are provided by lab bench test and design simulation. NOT test in production.

3.0-V to 5.5-V RS-485 Transceivers with 1.8-V I/O
Switching Characteristics, $V_{CC} = V_{IO} = 3.0\text{ V}$ (TPT4181H 20-Mbps)

Parameter		Conditions	Min	Typ	Max	Units
Driver						
t_r, t_f	Driver Differential-Output Rise and Fall Times ⁽¹⁾	$R_L = 54\ \Omega,$ $C_L = 50\ \text{pF}$	See Figure 2	10		ns
t_{PHL}, t_{PLH}	Driver Propagation Delay			22	40	
$t_{SK(P)}$	Driver Pulse Skew, $ t_{PHL} - t_{PLH} $			3	10	
t_{PHZ}	Driver Disable Time		See Figure 3	26	50	ns
t_{PLZ}				18	50	ns
t_{PZH}	Driver enable Time			30	50	ns
t_{PZL}				26	50	ns
Receiver						
t_{PHL}, t_{PLH}	Receiver Propagation Delay Time	$C_L = 15\ \text{pF}$	See Figure 5	40	80	ns
$t_{SK(P)}$	Receiver Pulse Skew, $ t_{PHL} - t_{PLH} $			7	15	
t_{PHZ}	Receiver Disable Time		See Figure 6	16	50	ns
t_{PLZ}				16	50	ns
t_{PZH}	Receiver Enable Time			80	125	ns
t_{PZL}				10	50	ns

(1) Parameters are provided by lab bench test and design simulation. NOT test in production.

Switching Characteristics, $V_{CC} = V_{IO} = 3.0\text{ V}$ (TPT4181V 500-Kbps)

Parameter	Conditions	Min	Typ	Max	Units
Driver					
t_r, t_f	Driver Differential-Output Rise and Fall Times ⁽¹⁾		400		ns
t_{PHL}, t_{PLH}	Driver Propagation Delay	$R_L = 54\ \Omega,$ $C_L = 50\ \text{pF}$	280	400	
$t_{SK(P)}$	Driver Pulse Skew, $ t_{PHL} - t_{PLH} $		5	20	
t_{PHZ}	Driver Disable Time		48	90	ns
t_{PLZ}				48	90
t_{PZH}	Driver Enable Time		300	500	ns
t_{PZL}				240	500
Receiver					
t_{PHL}, t_{PLH}	Receiver Propagation Delay Time	$C_L = 15\ \text{pF}$	110	200	ns
$t_{SK(P)}$	Receiver Pulse Skew, $ t_{PHL} - t_{PLH} $		15	28	
t_{PHZ}	Receiver Disable Time		16	50	ns
t_{PLZ}				16	50
t_{PZH}	Receiver Enable Time		135	180	ns
t_{PZL}				20	50

(1) Parameters are provided by lab bench test and design simulation. NOT test in production.


Test Circuits and Waveforms


Figure 1A. V_{OD} and V_{OC}








Figure 1B. V_{OD} with Common Mode Load

Figure 1. DC Driver Test Circuits


Figure 2A. Test Circuit

Figure 2B. Measurement Points
Figure 2. Driver Propagation Delay and Differential Transition Times

Figure 3A. Test Circuit

Figure 3B. Measurement Points

Parameter	Output	RE	DI	SW	CL (pF)
t _{PHZ}	A/B	X	1/0	GND	15
t _{PLZ}	A/B	X	0/1	V _{CC}	15
t _{PZH}	A/B	0	1/0	GND	100
t _{PZL}	A/B	0	0/1	V _{CC}	100
t _{PZH(SHDN)}	A/B	1	1/0	GND	100
t _{PZL(SHDN)}	A/B	1	0/1	V _{CC}	100

Figure 3. Driver Enable and Disable Times




Figure 4A. Test Circuit




Figure 4B. Measurement Points

Figure 4. Driver Data Rate




Figure 5A. Test Circuit




Figure 5B. Measurement Points

Figure 5. Receiver Propagation Delay and Data Rate




Figure 6A. Test Circuit





Figure 6B. Measurement Points

3.0-V to 5.5-V RS-485 Transceivers with 1.8-V I/O

Parameter	DE	A	SW
t_{PHZ}	1	+1.5 V	GND
t_{PLZ}	1	-1.5 V	V _{CC}
t_{PZH}	1	+1.5 V	GND
t_{PZL}	1	-1.5 V	V _{CC}
$t_{PZH} (SHDN)$	0	+1.5 V	GND
$t_{PZL} (SHDN)$	0	-1.5 V	V _{CC}

Figure 6. Receiver Enable and Disable Times


Tape and Reel Information



Order Number	Package	D1 (mm)	A0 (mm)	K0 (mm)	W0 (mm)	W1 (mm)	B0 (mm)	P0 (mm)	Pin1 Quadrant
TPT4181V-SO1R	SOP8	330.0	6.5	2.0	12.0	17.6	5.4	8.0	Q1
TPT4181H-SO1R	SOP8	330.0	6.5	2.0	12.0	17.6	5.4	8.0	Q1

Package Outline Dimensions

SOP8



Order Information

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPT4181V-SO1R	-40 to 125°C	SOP8	4181V	MSL1	Tape and Reel, 4000	Green
TPT4181H-SO1R	-40 to 125°C	SOP8	4181H	MSL1	Tape and Reel, 4000	Green

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2025. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.

This page intentionally left blank