

Features

- Data Rate: up to 100 Mbps
- Wide Supply Range: 2.25 V to 5.5 V
- Wide Temperature Range: -40°C to $+125^{\circ}\text{C}$
- Low Power Consumption: Typical 1.9 mA per Channel at 1 Mbps
- Low Propagation Delay: Typical 13 ns at 5 V Supply
- CMTI: Typical $\pm 200\text{ kV}/\mu\text{s}$ (Static), $\pm 150\text{ kV}/\mu\text{s}$ (Dynamic)
- Standout Transient Isolation Voltage: 12000 V_{PK} for WWSOP, 9191 V_{PK} for WSOP (100% Production)
- Standout Surge Immunity: 12000 V_{PK}
- Over 30-year Projected Lifetime under Working Voltage of 2000 V_{RMS} for WWSOP, 1500 V_{RMS} for WSOP
- Wide Creepage and Clearance: Nominal 15.0 mm for WWSOP, 8.0 mm for WSOP, 4.0 mm for SOP and QSOP
- Robust Electromagnetic Compatibility (EMC)
- Low Emissions, CISPR32 Class B Qualified
- System-level ESD and EFT Immunity
- Default Output High (TPT763x) and Low (TPT763xF)
- Wide Package Range: WSOP16, WWSOP16, SOP16, QSOP16
- Safety-related Certifications:
 - Reinforced Isolation according to DIN EN IEC 60747-17 (VDE 0884-17): 2021-10
 - Isolation for 1 Minute per UL 1577: 8000 V_{RMS} (WWSOP16), 6500 V_{RMS} (WSOP16), 3750 V_{RMS} (SOP16, QSOP16)
 - CQC Certification per GB 4943.1-2022
 - CSA Component Acceptance Notice 5A
 - CB Certification per IEC 62368-1: 2023

Applications

- Industrial Automation
- Motor Control
- Power Supplies
- Solar Inverters
- Isolated Interface and General-purpose Isolation

Description

The TPT763x devices are high-performance, 3-channel digital isolators with 8000 V_{RMS} (WWSOP16), 6500 V_{RMS} (WSOP16), and 3750 V_{RMS} (SOP16, QSOP16) isolation ratings per UL 1577. These devices are also certified by VDE, CSA Component Acceptance Notice 5A, CQC, and CB.

The TPT763x devices provide high reliability and high performance at low power consumption with isolating digital input and output. Each isolation signal channel is separated by a double capacitive silicon dioxide insulation barrier. The TPT7630 device has three channels in the forward direction. The TPT7631 device has two channels in the forward direction and one channel in the reverse direction. In the event of input power or signal loss, the default output is low for devices with the suffix F and high for devices without the suffix F.

The common mode transient immunity (CMTI) and electromagnetic compatibility of the TPT763x devices have been significantly enhanced through innovative circuit design and optimized structure.

The TPT763x family is available in SOP16, QSOP16, WSOP16, and WWSOP16 packages, and is characterized from -40°C to $+125^{\circ}\text{C}$.

Part Number	Package ⁽¹⁾	Body Size (Nominal)
TPT763x TPT763xF	SOP16	9.90 mm × 3.90 mm
	QSOP16	4.90 mm × 3.90 mm
	WSOP16	10.30 mm × 7.50 mm
	WWSOP16	10.30 mm × 14.00 mm

(1) For all available packages, see Order Information at the end of the datasheet.

Functional Block Diagram







Table of Contents

Features	1
Applications	1
Description	1
Functional Block Diagram	1
Revision History	3
Pin Configuration and Functions	4
Specifications	7
Absolute Maximum Ratings ⁽¹⁾	7
ESD, Electrostatic Discharge Protection.....	7
Recommended Operating Conditions.....	7
Thermal Information.....	8
Insulation Specifications.....	8
Safety-Related Certifications.....	11
Safety Limiting Values.....	12
Electrical Characteristics.....	13
Timing Specifications – 5 V Supply.....	14
Supply Current Characteristics – 5 V Supply.....	15
Timing Specifications – 3.3 V Supply.....	16
Supply Current Characteristics – 3.3 V Supply.....	17
Timing Specifications – 2.5 V Supply.....	18
Supply Current Characteristics – 2.5 V Supply.....	19
Test Circuits and Waveforms.....	20
Detailed Description	22
Overview.....	22
Functional Block Diagram.....	22
Feature Description.....	23
Application and Implementation	25
Typical Application.....	25
Tape and Reel Information	27
Package Outline Dimensions	29
SOP16.....	29
QSOP16.....	30
WSOP16.....	31
WWSOP16.....	32
Order Information	33
IMPORTANT NOTICE AND DISCLAIMER	34

Revision History

Date	Revision	Notes
2026-05-08	Rev.A.0	Initial version.
2026-07-22	Rev.A.1	The following updates are a about the new datasheet formats or typos, and the actual product remains unchanged. • Changed the power consumptionper channel in Features • Removed the supply Current Characteristics of the TPT7630 • Added superscripts to TPT7630 series in Order information

Pin Configuration and Functions




3-Channel Reinforced High-Performance Digital Isolator

TPT7631 / TPT7631F

SOP16


Top View



TPT7631 / TPT7631F

QSOP16


Top View



TPT7631 / TPT7631F

WSOP16, WWSOP16

Top View



3-Channel Reinforced High-Performance Digital Isolator

Table 1. Pin Functions: TPT763x

Pin		Name	I/O	Description
TPT7630 TPT7630F	TPT7631 TPT7631F			
1	1	VCCA	–	Power supply, VCCA
2	2	GNDA	–	Ground connection for VCCA
3	3	IN1	I	Input, channel 1
4	4	IN2	I	Input, channel 2
5	5	IN3	I	Input, channel 3
6, 7, 11	6, 11	NC	-	Not Connected
-	7	ENA	I	Side A enable pin
8	8	GNDA	–	Ground connection for VCCA
9	9	GNDB	–	Ground connection for VCCB
10	10	ENB	I	Side B enable pin
12	12	OUT3	O	Output, channel 3
13	13	OUT2	O	Output, channel 2
14	14	OUT1	O	Output, channel 1
15	15	GNDB	–	Ground connection for VCCB
16	16	VCCB	–	Power supply, VCCB

(1) ENA: Side-A OUTx are enabled when ENA is high or open, and in a high-impedance state when ENA is low.

(2) ENB: Side-B OUTx are enabled when ENB is high or open, and in a high-impedance state when ENB is low.

3-Channel Reinforced High-Performance Digital Isolator

Specifications

Absolute Maximum Ratings ⁽¹⁾

Parameter		Min	Max	Unit
V _{CC}	Supply Voltage, V _{CCA} , V _{CCB}	-0.5	6	V
V _{IO}	Voltage at IN _x , OUT _x , EN _x	-0.5	V _{CC} + 0.5	V
I _O	Output Current	-15	15	mA
T _J	Operating Virtual Junction Temperature	-	150	°C
T _{stg}	Storage Temperature	-65	150	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

ESD, Electrostatic Discharge Protection

Parameter		Condition	Value	Unit
HBM	HBM, per ANSI/ ESDA/ JEDEC JS-001/ ANSI/ ESD STM5.5.1 ⁽¹⁾	All Pins	±8	kV
CDM	CDM, per ANSI/ ESDA/ JEDEC JS-002 ⁽²⁾	All Pins	±2	kV
Latch-up	Latch-up, per JESD78	All Pins	±600	mA

(1) JEDEC document JEP155 states that 500 V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250 V CDM allows safe manufacturing with a standard ESD control process.

Recommended Operating Conditions

Parameter			Min	Typ	Max	Unit
V _{CCX}	Supply Voltage, V _{CCA} , V _{CCB} ⁽¹⁾		2.25	-	5.5	V
V _{CC(UVLO+)}	UVLO Threshold when Supply Voltage is rising ⁽²⁾		-	2	2.25	V
V _{CC(UVLO-)}	UVLO Threshold when Supply Voltage is falling ⁽²⁾		1.7	1.85	-	V
V _{HYS(UVLO)}	Supply Voltage UVLO Hysteresis		60	150	-	mV
I _{OH}	High-level Output Current	V _{CCB} = 5 V	−4	-	-	mA
		V _{CCB} = 3.3 V	−2	-	-	mA
		V _{CCB} = 2.5 V	−1	-	-	mA
I _{OL}	Low-level Output Current	V _{CCB} = 5 V	-	-	4	mA
		V _{CCB} = 3.3 V	-	-	2	mA
		V _{CCB} = 2.5 V	-	-	1	mA
V _{IH}	High-level Input Voltage (data input)		0.7 * V _{CC}	-	V _{CC}	V
V _{IL}	Low-level Input Voltage (data input)		0	-	0.3 * V _{CC}	V

3-Channel Reinforced High-Performance Digital Isolator

Parameter		Min	Typ	Max	Unit
f _{data}	Data Rate ⁽³⁾	0	-	100	Mbps
T _A	Operating Ambient Temperature	-40	25	125	°C

(1) V_{CCA} is the input side V_{CC}; V_{CCB} is the output side V_{CC};

(2) V_{CC(UVLO+)}, V_{CC(UVLO-)}, V_{HYS(UVLO)} are same to V_{CCA} and V_{CCB};

(3) 100 Mbps is the data rate tested in the lab, although higher data rates are possible.

Thermal Information

Package Type	θ _{JA}	θ _{JC}	Unit
SOP16	58.79	27.28	°C/W
QSOP16	76.74	35.60	°C/W
WSOP16	59.09	22.58	°C/W
WWSOP16	50.24	18.77	°C/W

Insulation Specifications

Parameter		Test Conditions	Value				Unit
			SOP16	QSOP16	WSOP16	WWSOP16	
IEC 60664-1							
CLR	External clearance (1)	Shortest terminal-to-terminal distance through air, nominal	4	4	8	15	mm
CPG	External creepage (1)	Shortest terminal-to-terminal distance across the package surface, nominal	4	4	8	15	mm
DTI	Distance through the insulation	Minimum internal gap (internal clearance)	> 22	> 22	> 22	> 22	μm
DTC	Distance through the Molding compound	Minimum internal distance across the conductors inside the package	0.45	0.45	0.8	0.8	mm
CTI	Comparative tracking index	IEC 60112	> 600	> 600	> 600	> 600	V
	Material group	According to IEC 60664-1	I	I	I	I	
	Overvoltage category per IEC 60664-1	Rated mains voltage ≤ 150 V _{RMS}	I-IV	I-IV	I-IV	I-IV	
		Rated mains voltage ≤ 300 V _{RMS}	I-III	I-III	I-IV	I-IV	
		Rated mains voltage ≤ 600 V _{RMS}	I-II	I-II	I-IV	I-IV	
		Rated mains voltage ≤ 1000 V _{RMS}	I	I	I-III	I-IV	
DIN EN IEC 60747-17 (VDE 0884-17) (2)							
V _{IORM}	Maximum repetitive peak isolation voltage	AC voltage (bipolar)	707	707	2121	2828	V _{PK}

3-Channel Reinforced High-Performance Digital Isolator

Parameter		Test Conditions	Value				Unit
			SOP16	QSOP16	WSOP16	WWSOP 16	
V _{IOWM}	Maximum working isolation voltage	AC voltage; Time-dependent dielectric breakdown (TDDb) Test	500	500	1500	2000	V _{RMS}
		DC voltage	707	707	2121	2828	V _{DC}
V _{IOTM}	Maximum transient isolation voltage	V _{TEST} = V _{IOTM} , t = 60 s (qualification); V _{TEST} = 1.2 × V _{IOTM} , t = 1 s (100% production)	5300	5300	9191	12000	V _{PK}
V _{IMP}	Maximum impulse voltage ⁽³⁾	Tested in air, 1.2/50 μs waveform per IEC 62368-1	8000	8000	9000	9000	V _{PK}
V _{IOSM}	Maximum surge isolation voltage ⁽⁴⁾	V _{IOSM} ≥ 1.3 × V _{IMP} ; tested in oil (qualification test), 1.2/50 μs waveform per IEC 62368-1	12000	12000	12000	12000	V _{PK}
q _{pd}	Apparent charge ⁽⁵⁾	Method a, After input-output safety test subgroup 2/3, V _{ini} = V _{IOTM} , t _{ini} = 60 s; V _{pd(m)} = 1.2 × V _{IORM} , t _m = 10 s	≤ 5	≤ 5	≤ 5	≤ 5	pC
		Method a, After environmental tests subgroup 1, V _{ini} = V _{IOTM} , t _{ini} = 60 s; V _{pd(m)} = 1.6 × V _{IORM} , t _m = 10 s	≤ 5	≤ 5	≤ 5	≤ 5	
		Method b: At routine test (100% production); V _{ini} = 1.2 × V _{IOTM} , t _{ini} = 1 s; V _{pd(m)} = 1.875 × V _{IORM} , t _m = 1 s (method b1) or V _{pd(m)} = V _{ini} , t _m = t _{ini} (method b2)	≤ 5	≤ 5	≤ 5	≤ 5	
C _{IO}	Barrier capacitance, input to output ⁽⁶⁾	V _{IO} = 0.4 × sin (2πft), f = 1 MHz	~0.5	~0.5	~0.5	~0.5	pF
R _{IO}	Isolation resistance, input to output ⁽⁶⁾	V _{IO} = 500 V, T _A = 25°C	> 10 ¹²	> 10 ¹²	> 10 ¹²	> 10 ¹²	Ω
		V _{IO} = 500 V, 100°C ≤ T _A ≤ 125°C	> 10 ¹¹	> 10 ¹¹	> 10 ¹¹	> 10 ¹¹	Ω
		V _{IO} = 500 V at T _S = 150°C	> 10 ⁹	> 10 ⁹	> 10 ⁹	> 10 ⁹	Ω
	Pollution degree		2	2	2	2	
	Climatic category		-40/125/21	-40/125/21	-40/125/21	-40/125/21	
UL 1577							
V _{ISO}	Withstand isolation voltage	V _{TEST} = V _{ISO} , t = 60 s (qualification); V _{TEST} = 1.2 × V _{ISO} , t = 1 s (100% production)	3750	3750	6500	8000	V _{RMS}

(1) Creepage and clearance requirements should be applied according to the specific equipment isolation standards of an application. Care should be taken to maintain the creepage and clearance distance of a board design to ensure that the mounting pads of the isolator on the printed-circuit board do not reduce this distance. Creepage and clearance on a printed-circuit board become equal in certain cases. Techniques such as inserting grooves, ribs, or both on a printed circuit board are used to help increase these specifications.

3-Channel Reinforced High-Performance Digital Isolator

- (2) This coupler is suitable for safe electrical insulation only within the safety ratings. Compliance with the safety ratings shall be ensured by means of suitable protective circuits.
- (3) Testing is carried out in air to determine the surge immunity of the package.
- (4) Testing is carried out in oil to determine the intrinsic surge immunity of the isolation barrier.
- (5) Apparent charge is electrical discharge caused by a partial discharge (pd).
- (6) All pins on each side of the barrier are tied together creating a two-pin device.

3-Channel Reinforced High-Performance Digital Isolator**Safety-Related Certifications**

VDE	cUL		CQC	CB
Plan to certify according to DIN EN IEC 60747-17 (VDE 0884-17): 2021-10	Plan to certify according to UL 1577, Edition 5	Plan to certify according to CSA Component Acceptance Notice 5A	Plan to certify according to GB 4943.1-2022	Plan to certify according to EN IEC 62368-1: 2023
Certificate planned	Certificate planned	Certificate planned	Certificate planned	Certificate planned

Safety Limiting Values

Safety limiting ⁽¹⁾ intends to minimize potential damage to the isolation barrier upon failure of input or output circuitry.

Parameter	Conditions	Min	Typ	Max	Unit
I _S	R _{θJA} = 58.79°C/W, V _I = 5 V, T _J = 150°C, T _A = 25°C (SOP16)	-	-	425.24	mA
	R _{θJA} = 76.74°C/W, V _I = 5 V, T _J = 150°C, T _A = 25°C (QSOP16)	-	-	325.78	
	R _{θJA} = 59.09°C/W, V _I = 5 V, T _J = 150°C, T _A = 25°C (WSOP16)	-	-	423.08	
	R _{θJA} = 50.24°C/W, V _I = 5 V, T _J = 150°C, T _A = 25°C (WWSOP16)	-	-	497.61	
P _S	R _{θJA} = 58.79°C/W, T _J = 150°C, T _A = 25°C (SOP16)	-	-	2126.21	mW
	R _{θJA} = 76.74°C/W, T _J = 150°C, T _A = 25°C (QSOP16)	-	-	1628.88	
	R _{θJA} = 59.09°C/W, T _J = 150°C, T _A = 25°C (WSOP16)	-	-	2115.42	
	R _{θJA} = 50.24°C/W, T _J = 150°C, T _A = 25°C (WWSOP16)	-	-	2488.06	
T _S	Maximum Safety Temperature	-	-	150	°C

(1) The maximum safety temperature, T_S, has the same value as the maximum junction temperature, T_J, specified for the device. The I_S and P_S parameters represent the safety current and safety power respectively. The maximum limits of I_S and P_S must not be exceeded. These limits vary with the ambient temperature, T_A.

The junction-to-air thermal resistance, R_{θJA}, in the table is that of a device installed on a high-K test board for leaded surface-mount packages. Use these equations to calculate the value for each parameter:

$T_J = T_A + R_{\theta JA} \times P$, where P is the power dissipated in the device.

$T_{J(max)} = T_S = T_A + R_{\theta JA} \times P_S$, where T_{J(max)} is the maximum allowed junction temperature.

$P_S = I_S \times V_I$, where V_I is the maximum input voltage.

3-Channel Reinforced High-Performance Digital Isolator

Electrical Characteristics

All test conditions: $V_{CCA} = V_{CCB} = 2.25 \text{ V to } 5.5 \text{ V}$, and $T_A = -40^\circ\text{C to } +125^\circ\text{C}$. Typical value is at $V_{CC} = 3.3 \text{ V}$, $T_A = +25^\circ\text{C}$, unless otherwise noted.

Parameter		Conditions	Min	Typ	Max	Unit
V_{IT+}	Rising Input Threshold Voltage	Input signal, INx	-	0.52 * $V_{CCI}^{(1)}$	0.7 * V_{CCI}	V
V_{IT-}	Falling Input Threshold Voltage	Input signal, INx	0.3 * V_{CCI}	0.38 * V_{CCI}	-	V
V_{HYS}	Input Threshold Voltage Hysteresis		-	0.14 * V_{CCI}	-	V
I_{IH}	High-level Input Current	$V_{IH} = V_{CCA}$ at INx ⁽¹⁾	0	6.2	20	μA
I_{IL}	Low-level Input Current	$V_{IL} = 0 \text{ V}$ at INx ⁽¹⁾	-1	0	1	μA
V_{OH}	High-level Output Voltage	$V_{CCO}^{(1)} = 5 \text{ V} \pm 10\%$, $I_{OH} = -4 \text{ mA}$; Test OUTx	$V_{CCB} - 0.4$	$V_{CCB} - 0.2$	-	V
		$V_{CCO} = 3.3 \text{ V} \pm 10\%$, $I_{OH} = -2 \text{ mA}$; Test OUTx	$V_{CCB} - 0.2$	$V_{CCB} - 0.11$	-	
		$V_{CCO} = 2.5 \text{ V} \pm 10\%$, $I_{OH} = -1 \text{ mA}$; Test OUTx	$V_{CCB} - 0.1$	$V_{CCB} - 0.07$	-	
V_{OL}	Low-level Output Voltage	$V_{CCO} = 5 \text{ V} \pm 10\%$, $I_{OL} = 4 \text{ mA}$; Test OUTx	-	0.17	0.4	V
		$V_{CCO} = 3.3 \text{ V} \pm 10\%$, $I_{OL} = 2 \text{ mA}$; Test OUTx	-	0.1	0.2	
		$V_{CCO} = 2.5 \text{ V} \pm 10\%$, $I_{OL} = 1 \text{ mA}$; Test OUTx	-	0.05	0.1	
CMTI	Common-mode Transient Immunity	Static CMTI	-	200	-	kV/ μs
		Dynamic CMTI	-	150	-	kV/ μs
C_i	Input Capacitance ⁽²⁾		-	2.8	-	pF

(1) V_{CCI} = Input-side V_{CC} ; V_{CCO} = Output-side V_{CC}

(2) Provided by bench test and design simulation.

3-Channel Reinforced High-Performance Digital Isolator

Timing Specifications – 5 V Supply

All test conditions: $V_{CCA} = V_{CCB} = 5\text{ V} \pm 10\%$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$. Typical value is at $V_{CC} = 5\text{ V}$, $T_A = +25^\circ\text{C}$, $C_L = 15\text{ pF}$ to GND, unless otherwise noted.

Parameter		Conditions	Min	Typ	Max	Unit
f_{DATA}	Translation data rate		-	-	100	Mbps
t_{PLH}	Propagation delay time, low-to-high		8	13	24	ns
t_{PHL}	Propagation delay time, high-to-low		8	13	24	ns
PWD	Pulse width distortion ⁽¹⁾ $ t_{\text{PHL}} - t_{\text{PLH}} $		-	0.5	7	ns
$t_{\text{sk(CC)}}$	Channel-to-channel output skew time ⁽¹⁾⁽²⁾	Same direction channels	-	3.8	6	ns
$t_{\text{sk(PP)}}$	Part-to-part output skew time ⁽¹⁾⁽²⁾	Same direction channels	-	-	6	ns
t_r	Output signal rise time ⁽¹⁾		-	1.6	10	ns
t_f	Output signal fall time ⁽¹⁾		-	1.3	10	ns
t_{PHZ}	Disable propagation delay, high-to-high impedance output	$C_L = 15\text{ pF}$, $R_L = 1\text{ k}\Omega$	-	8	40	ns
t_{PLZ}	Disable propagation delay, low-to-high impedance output	$C_L = 15\text{ pF}$, $R_L = 1\text{ k}\Omega$	-	7	40	ns
t_{PZH}	Enable propagation delay, high impedance-to-high output	$C_L = 15\text{ pF}$, $R_L = 1\text{ k}\Omega$	-	7	40	ns
t_{PZL}	Enable propagation delay, high impedance-to-low output	$C_L = 15\text{ pF}$, $R_L = 1\text{ k}\Omega$	-	7	40	ns
t_{DO}	Default output delay time from input power loss	Measured from the time V_{CC} goes below 1.7 V	-	34	80	ns
t_{SU}	Setup time		1	35	80	μs

(1) Provided by bench test and design simulation.

(2) $t_{\text{sk(CC)}}$ is the skew of delay time between different channels of a single device, while $t_{\text{sk(PP)}}$ is the skew of delay time between different devices switching in the same direction while operating at identical supply voltages, temperature, input signals, and loads.

3-Channel Reinforced High-Performance Digital Isolator

Supply Current Characteristics – 5 V Supply

All test conditions: $V_{CCA} = V_{CCB} = 5\text{ V} \pm 10\%$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$. Typical value is at $V_{CC} = 5\text{ V}$, $T_A = +25^\circ\text{C}$, $C_L = 15\text{ pF}$ to GND, unless otherwise noted.

Parameter	Description		Supply Current	Min	Typ	Max	Unit
TPT7631							
Supply current - DC signal	$V_I = 0\text{ V}$ (TPT7631F) $V_I = V_{CC_I}$ (TPT7631)		I_{CCA}	-	1.8	2.8	mA
			I_{CCB}	-	1.8	2.8	
	$V_I = V_{CC_I}$ (TPT7631F) $V_I = 0\text{ V}$ (TPT7631)		I_{CCA}	-	4.4	6.0	
			I_{CCB}	-	3.1	6.0	
Supply current - AC signal	All channels switching with square wave clock input; $C_L = 15\text{ pF}$	1 Mbps	I_{CCA}	-	3.1	4.7	
			I_{CCB}	-	2.5	4.7	
		10 Mbps	I_{CCA}	-	3.6	5.9	
			I_{CCB}	-	3.4	5.9	
		100 Mbps	$I_{CCA}^{(1)}$	-	8.8	-	
			$I_{CCB}^{(1)}$	-	11.6	-	

(1) Provided by bench test and design simulation.

3-Channel Reinforced High-Performance Digital Isolator

Timing Specifications – 3.3 V Supply

All test conditions: $V_{CCA} = V_{CCB} = 3.3 \text{ V} \pm 10\%$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$. Typical value is at $V_{CC} = 3.3 \text{ V}$, $T_A = +25^\circ\text{C}$, $C_L = 15 \text{ pF}$ to GND, unless otherwise noted.

Parameter		Conditions	Min	Typ	Max	Unit
f_{DATA}	Translation data rate		-	-	100	Mbps
t_{PLH}	Propagation delay time, low-to-high		-	18	24	ns
t_{PHL}	Propagation delay time, high-to-low		-	17	24	ns
PWD	Pulse width distortion ⁽¹⁾ $ t_{\text{PHL}} - t_{\text{PLH}} $		-	0.8	5	ns
$t_{\text{sk(CC)}}$	Channel-to-channel output skew time ⁽¹⁾⁽²⁾	Same direction channels	-	-	2.5	ns
$t_{\text{sk(PP)}}$	Part-to-part output skew time ⁽¹⁾⁽²⁾	Same direction channels	-	-	4.5	ns
t_r	Output signal rise time ⁽¹⁾		-	2	4	ns
t_f	Output signal fall time ⁽¹⁾		-	2	4	ns
t_{PHZ}	Disable propagation delay, high-to-high impedance output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	-	10	40	ns
t_{PLZ}	Disable propagation delay, low-to-high impedance output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	-	10	40	ns
t_{PZH}	Enable propagation delay, high impedance-to-high output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	-	10	40	ns
t_{PZL}	Enable propagation delay, high impedance-to-low output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	-	10	40	ns
t_{DO}	Default output delay time from input power loss	Measured from the time V_{CC} goes below 1.7 V.	-	30	80	ns
t_{SU}	Setup time		-	28	80	μs

(1) Provided by bench test and design simulation.

(2) $t_{\text{sk(CC)}}$ is the skew of delay time between different channels of a single device, while $t_{\text{sk(PP)}}$ is the skew of delay time between different devices switching in the same direction while operating at identical supply voltages, temperature, input signals, and loads.

3-Channel Reinforced High-Performance Digital Isolator

Supply Current Characteristics – 3.3 V Supply

All test conditions: $V_{CCA} = V_{CCB} = 3.3 \text{ V} \pm 10\%$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$. Typical value is at $V_{CC} = 3.3 \text{ V}$, $T_A = +25^\circ\text{C}$, $C_L = 15 \text{ pF}$ to GND, unless otherwise noted.

Parameter	Description		Supply Current	Min	Typ	Max	Unit
TPT7631							
Supply current - DC signal	V _I = 0 V (TPT7631F) V _I = V _{CC_I} (TPT7631)		I _{CCA}	-	1.8	2.6	mA
			I _{CCB}	-	1.8	2.6	
	V _I = V _{CC_I} (TPT7631F) V _I = 0 V (TPT7631)		I _{CCA}	-	4.4	5.8	
			I _{CCB}	-	3.1	5.8	
Supply current - AC signal	All channels switching with square wave clock input; C _L = 15 pF	1 Mbps	I _{CCA}	-	3.1	4.4	
			I _{CCB}	-	2.5	4.4	
		10 Mbps	I _{CCA}	-	3.4	5.2	
			I _{CCB}	-	3.0	5.2	
		100 Mbps	I _{CCA} ⁽¹⁾	-	6.9	-	
			I _{CCB} ⁽¹⁾	-	8.4	-	

(1) Provided by bench test and design simulation.

3-Channel Reinforced High-Performance Digital Isolator

Timing Specifications – 2.5 V Supply

All test conditions: $V_{CCA} = V_{CCB} = 2.5 \text{ V} \pm 10\%$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$. Typical value is at $V_{CC} = 2.5 \text{ V}$, $T_A = +25^\circ\text{C}$, $C_L = 15 \text{ pF}$ to GND, unless otherwise noted.

Parameter		Conditions	Min	Typ	Max	Unit
f_{DATA}	Translation data rate		-	-	100	Mbps
t_{PLH}	Propagation delay time, low-to-high		8	15	24	ns
t_{PHL}	Propagation delay time, high-to-low		8	15	24	ns
PWD	Pulse width distortion ⁽¹⁾ $ t_{\text{PHL}} - t_{\text{PLH}} $		-	0.6	7	ns
$t_{\text{sk(CC)}}$	Channel-to-channel output skew time ⁽¹⁾⁽²⁾	Same direction channels	-	3	6	ns
$t_{\text{sk(PP)}}$	Part-to-part output skew time ⁽¹⁾⁽²⁾	Same direction channels	-	-	6	ns
t_r	Output signal rise time ⁽¹⁾		-	2.3	10	ns
t_f	Output signal fall time ⁽¹⁾		-	1.5	10	ns
t_{PHZ}	Disable propagation delay, high-to-high impedance output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	1	12	30	ns
t_{PLZ}	Disable propagation delay, low-to-high impedance output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	1	14	30	ns
t_{PZH}	Enable propagation delay, high impedance-to-high output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	1	12	30	ns
t_{PZL}	Enable propagation delay, high impedance-to-low output	$C_L = 15 \text{ pF}$, $R_L = 1 \text{ k}\Omega$	1	12	30	ns
t_{DO}	Default output delay time from input power loss	Measured from the time V_{CC} goes below 1.7 V.	-	29	80	ns
t_{SU}	Setup time		1	35	80	μs

(1) Provided by bench test and design simulation.

(2) $t_{\text{sk(CC)}}$ is the skew of delay time between different channels of a single device, while $t_{\text{sk(PP)}}$ is the skew of delay time between different devices switching in the same direction while operating at identical supply voltages, temperature, input signals, and loads.

3-Channel Reinforced High-Performance Digital Isolator

Supply Current Characteristics – 2.5 V Supply

All test conditions: $V_{CCA} = V_{CCB} = 2.5 \text{ V} \pm 10\%$, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$. Typical value is at $V_{CC} = 2.5 \text{ V}$, $T_A = +25^\circ\text{C}$, $C_L = 15 \text{ pF}$ to GND, unless otherwise noted.

Parameter	Description		Supply Current	Min	Typ	Max	Unit
TPT7631							
Supply current - DC signal	V _I = 0 V (TPT7631F) V _I = VCC _I (TPT7631)		I _{CCA}	-	1.7	2.5	mA
			I _{CCB}	-	1.8	2.5	
	V _I = VCC _I (TPT7631F) V _I = 0 V (TPT7631)		I _{CCA}	-	4.4	5.7	
			I _{CCB}	-	3.1	5.7	
Supply current - AC signal	All channels switching with square wave clock input; C _L = 15 pF	1 Mbps	I _{CCA}	-	3.1	4.3	
			I _{CCB}	-	2.5	4.3	
		10 Mbps	I _{CCA}	-	3.3	5.0	
			I _{CCB}	-	2.9	5.0	
		100 Mbps	I _{CCA} ⁽¹⁾	-	6.1	-	
			I _{CCB} ⁽¹⁾	-	7.0	-	

(1) Provided by bench test and design simulation.

Test Circuits and Waveforms




Figure 1. Switching Characteristics Test Circuit and Waveforms




Figure 2. Default Output Delay Time Test Circuit and Voltage Waveforms




Figure 3. Enable/Disable Propagation Delay Test Circuit and Waveforms

3-Channel Reinforced High-Performance Digital Isolator




Figure 4. Common-Mode Transient Immunity Test Circuit

Detailed Description

Overview

The TPT763x device utilizes an ON-OFF Keying (OOK) modulation circuit to transmit the digital data through the isolation barrier. The transmitter sends an HF carrier to represent the digital state One and sends no signal to represent the digital state Zero. Once the modulated signal passes through the barrier, the receiver demodulates the signal following the process of signal conditioning and brings the output via a buffer stage. If the EN pin is at a Low level, the output goes to the high-impedance state. The device also utilizes advanced circuit design to maximize the CMTI performance and minimize the radiated emissions due to the HF carrier and IO buffer switching. The block diagram below shows a functional block diagram of a typical channel.

Functional Block Diagram




Figure 5. Block Diagram of Digital Capacitive Isolator




Figure 6. On-Off Keying (OOK) based Modulation Scheme

3-Channel Reinforced High-Performance Digital Isolator

Feature Description

The TPT763x device is available in two-channel configurations and has two default output state options to enable a variety of application uses. The table below lists the device features of the TPT763x device.

Part Number	Max Data Rate	Channel Direction	Default Output State	Package	Rating Isolation
TPT7630	100 Mbps	3 forward, 0 reverse	High	SOP16	3750 V _{RMS} / 5300 V _{PK}
				QSOP16	3750 V _{RMS} / 5300 V _{PK}
				WSOP16	6500 V _{RMS} / 9191 V _{PK}
				WWSOP16	8000 V _{RMS} / 12000 V _{PK}
TPT7630F	100 Mbps	3 forward, 0 reverse	Low	SOP16	3750 V _{RMS} / 5300 V _{PK}
				QSOP16	3750 V _{RMS} / 5300 V _{PK}
				WSOP16	6500 V _{RMS} / 9191 V _{PK}
				WWSOP16	8000 V _{RMS} / 12000 V _{PK}
TPT7631	100 Mbps	2 forward, 1 reverse	High	SOP16	3750 V _{RMS} / 5300 V _{PK}
				QSOP16	3750 V _{RMS} / 5300 V _{PK}
				WSOP16	6500 V _{RMS} / 9191 V _{PK}
				WWSOP16	8000 V _{RMS} / 12000 V _{PK}
TPT7631F	100 Mbps	2 forward, 1 reverse	Low	SOP16	3750 V _{RMS} / 5300 V _{PK}
				QSOP16	3750 V _{RMS} / 5300 V _{PK}
				WSOP16	6500 V _{RMS} / 9191 V _{PK}
				WWSOP16	8000 V _{RMS} / 12000 V _{PK}

3-Channel Reinforced High-Performance Digital Isolator

Device Functional Modes

The table below lists the functional modes for the TPT763x device.

VCC _I	VCC _O	Input (IN _x)	Enable (EN _A , EN _B)	Output (OUT _x)	Comments
Power up	Power up	High	High or Open	High	Normal Operation.
		Low	High or Open	Low	
		Open	High or Open	Default	Default mode. The default is High for TPT763x and Low for TPT763xF.
X	Power up	X	Low	Z	Disabled output is in high impedance.
Power down	Power up	X	High or Open	Default	Default mode. When VCC _I is unpowered, the default is High for TPT763x and Low for TPT763xF.
X	Power down	X	X	Undetermined	When VCC _O is unpowered, a channel output is undetermined.

(1) VCC_I = Input-side V_{CCA}; VCC_O = Output-side V_{CCB}; Power up means V_{CC} ≥ 2.25 V; Power down means V_{CC} ≤ 1.7 V; X = Irrelevant; Z = High impedance

(2) The outputs are in the undetermined state when 1.7 V < VCC_I & VCC_O < 2.25 V.

3-Channel Reinforced High-Performance Digital Isolator

Application and Implementation

Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Typical Application

Figure 7 is the TPT763x typical application. The two external bypass capacitors need to be close to the VCC power pin. The maximum distance is 2 mm.




Figure 7. TPT7630/TPT7630F

3-Channel Reinforced High-Performance Digital Isolator





Figure 8. TPT7631/TPT7631F

3-Channel Reinforced High-Performance Digital Isolator

Tape and Reel Information





3-Channel Reinforced High-Performance Digital Isolator

Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	W0 (mm)	Pin1 Quadrant
TPT7630-SO3R	SOP16	330	21.6	6.6	10.4	2.1	8.0	16.0	Q1
TPT7630F-SO3R	SOP16	330	21.6	6.6	10.4	2.1	8.0	16.0	Q1
TPT7631-SO3R	SOP16	330	21.6	6.6	10.4	2.1	8.0	16.0	Q1
TPT7631F-SO3R	SOP16	330	21.6	6.6	10.4	2.1	8.0	16.0	Q1
TPT7630-SSAR	QSOP16	330	17.6	6.5	5.4	2.0	8.0	12.0	Q1
TPT7630F-SSAR	QSOP16	330	17.6	6.5	5.4	2.0	8.0	12.0	Q1
TPT7631-SSAR	QSOP16	330	17.6	6.5	5.4	2.0	8.0	12.0	Q1
TPT7631F-SSAR	QSOP16	330	17.6	6.5	5.4	2.0	8.0	12.0	Q1
TPT7630-SOBR	WSOP16	330	21.6	10.9	10.8	3.1	12.0	16.0	Q1
TPT7630F-SOBR	WSOP16	330	21.6	10.9	10.8	3.1	12.0	16.0	Q1
TPT7631-SOBR	WSOP16	330	21.6	10.9	10.8	3.1	12.0	16.0	Q1
TPT7631F-SOBR	WSOP16	330	21.6	10.9	10.8	3.1	12.0	16.0	Q1
TPT7630-SOFR	WWSOP16	330	29.0	17.6	10.8	3.0	20.0	24.0	Q1
TPT7630F-SOFR	WWSOP16	330	29.0	17.6	10.8	3.0	20.0	24.0	Q1
TPT7631-SOFR	WWSOP16	330	29.0	17.6	10.8	3.0	20.0	24.0	Q1
TPT7631F-SOFR	WWSOP16	330	29.0	17.6	10.8	3.0	20.0	24.0	Q1

Package Outline Dimensions

SOP16



QSOP16
Package Outline Dimensions
SSA(QSOP-16-A)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	1.350	1.750	0.053	0.069
A1	0.050	0.250	0.002	0.010
A2	1.300	1.500	0.051	0.059
b	0.230	0.310	0.009	0.012
c	0.170	0.250	0.007	0.010
D	4.800	5.000	0.189	0.197
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
e	0.635 BSC		0.025 BSC	
L	0.400	0.800	0.016	0.031
θ	0	8°	0	8°

NOTES


1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

3-Channel Reinforced High-Performance Digital Isolator

WSOP16

Package Outline Dimensions




SOB(WSOP-16-A)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	2.350	2.650	0.093	0.104
A1	0.100	0.300	0.004	0.012
A2	2.250	2.350	0.089	0.093
b	0.350	0.450	0.014	0.018
c	0.200	0.290	0.008	0.011
D	10.100	10.500	0.398	0.413
E	10.100	10.600	0.398	0.417
E1	7.300	7.700	0.287	0.303
e	1.270 BSC		0.050 BSC	
L	0.500	0.850	0.020	0.033
θ	0	8°	0	8°

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

WWSOP16
Package Outline Dimensions
SOF(WWSOP-16-A)

NOTES

1. Do not include mold flash or protrusion.
2. This drawing is subject to change without notice.

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	---	2.650	---	0.104
A1	0.100	0.300	0.004	0.012
A2	2.236	2.336	0.088	0.092
b	0.310	0.510	0.012	0.020
c	0.220	0.280	0.009	0.011
D	10.200	10.400	0.402	0.409
E	17.100	17.400	0.673	0.685
E1	13.900	14.100	0.547	0.555
e	1.270 BSC		0.050 BSC	
L	0.600	1.100	0.024	0.043
θ	0	8°	0	8°

3-Channel Reinforced High-Performance Digital Isolator

Order Information

Part number	Operating temperature range	Package	Marking	MSL	Transport media & quantity	Eco plan
TPT7630-SO3R ⁽¹⁾	-40 to 125°C	SOP16	T7630	MSL3	Tape and Reel, 2500	Green
TPT7630F-SO3R ⁽¹⁾	-40 to 125°C	SOP16	7630F	MSL3	Tape and Reel, 2500	Green
TPT7631-SO3R	-40 to 125°C	SOP16	T7631	MSL3	Tape and Reel, 2500	Green
TPT7631F-SO3R	-40 to 125°C	SOP16	7631F	MSL3	Tape and Reel, 2500	Green
TPT7630-SSAR ⁽¹⁾	-40 to 125°C	QSOP16	T7630	MSL3	Tape and Reel, 4000	Green
TPT7630F-SSAR ⁽¹⁾	-40 to 125°C	QSOP16	7630F	MSL3	Tape and Reel, 4000	Green
TPT7631-SSAR	-40 to 125°C	QSOP16	T7631	MSL3	Tape and Reel, 4000	Green
TPT7631F-SSAR	-40 to 125°C	QSOP16	7631F	MSL3	Tape and Reel, 4000	Green
TPT7630-SOBR ⁽¹⁾	-40 to 125°C	WSOP16	T7630	MSL3	Tape and Reel, 1500	Green
TPT7630F-SOBR ⁽¹⁾	-40 to 125°C	WSOP16	7630F	MSL3	Tape and Reel, 1500	Green
TPT7631-SOBR	-40 to 125°C	WSOP16	T7631	MSL3	Tape and Reel, 1500	Green
TPT7631F-SOBR	-40 to 125°C	WSOP16	7631F	MSL3	Tape and Reel, 1500	Green
TPT7630-SOFR ⁽¹⁾	-40 to 125°C	WWSOP16	T7630	MSL3	Tape and Reel, 1000	Green
TPT7630F-SOFR ⁽¹⁾	-40 to 125°C	WWSOP16	7630F	MSL3	Tape and Reel, 1000	Green
TPT7631-SOFR	-40 to 125°C	WWSOP16	T7631	MSL3	Tape and Reel, 1000	Green
TPT7631F-SOFR	-40 to 125°C	WWSOP16	7631F	MSL3	Tape and Reel, 1000	Green

(1) For future products, contact the 3PEAK factory for more information and samples.

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2026. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.